



WWW.DELOCK.COM

DATA SHEET



# Slot bracket USB 3.0 pin header 19 pin

+ SATA 7 pin internal > 1 x USB 3.0-A

+ 1 x Multiport external

### **Description**

This slot bracket by Delock can be installed into a standard PC slot and expands your system by an external Multiport. The Multiport interface is a combination of USB 3.0 and eSATAp, which offers a number of connecting options. Thus the Multiport enables you to connect devices, like e.g. Hubs, Card reader, external enclosure etc. with the following interface:

- 1. USB 3.0
- 2. USB 2.0
- 3. eSATAp (Power Over eSATA 5 V)
- 4. eSATA



Ref. 82977

EAN 4043619829774

Country of origin China
Customs tariff number 84718000

## **Specification**

• Connector: internal 1 x 19 pin USB 3.0 pin header female

+ SATA 7 pin

external 1 x USB 3.0-A female 1 x Multiport female

Cable gauge: 28 AWG

· Current output: max. 900 mA per each USB port

• Voltage: 5 V

 Data transfer rate up to: Super-Speed 5 Gb/s, High-Speed 480 MB/s
 Full-Speed 12 Mb/s, Low-Speed 1.5 Mb/s, eSATA 3 Gb/s

- Downwards compatible to USB 2.0 and USB 1.1
- Cable length: ca. 45 cm (without connector)

#### System requirement

- PC with a free slot
- Mainboard with a free 19 pin USB 3.0 pin header connector and a free SATA port

**Note**: For operation of two devices at the same time, which equire more than 900 mA for each device, you may need to connect an additional power supply for the connected device.

#### Package content

Slot bracket

#### **Package**

Delock poly bag

© 2011 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.