

# Delock USB WLAN 2 T 2 R 300 Mbps 3 V

## Description

The Delock USB module offers in a compact construction WLAN function via USB interface and is ideal for installation in industry components like sensors, IPCs, PDAs or notebooks.



### Item no. 95905

EAN: 4043619959051

Country of origin:

Package: Poly bag

## Specification

- USB 2.0 interface
- 6 pin SMT female port suitable for item 95835 cable
- WLAN IEEE 802.11n and IEEE 802.11 b/g
- Chipset: Ralink RT3072 MAC/BBP/RF
- Voltage: 3,3 V (+/- 0,3 V)
- Low power consumption
- Operating temperature: 0° ~ 65 °C
- 11b: 1,2,5.5,11Mbps
- 11g: 6,9,12,18,24,36,48,54Mbps
- 11n: legacy and high throughput modes
- Band width: 20/40 MHz, MCS0~7(300 Mbps PHY Rate)
- WEP 64/128, WPA, WPA2, TKIP, AES
- QoS-WMM, WMM-PS
- WPS, PIN, PBC
- multiple BSSID support
- LED indicator for status connection
- Dimension: 34 x 15 x 5.90 mm (LxWxH)
- 2T2R 2 antenna connection I-PEX

## System requirements

- Windows CE/2000/XP/Vista7, Linux, Mac OS

---

## Package content

- Module

---

## Images

