



PIN ASSIGNMENT

HDMI 19M	HDMI 19F	HDMI 19F
3	3	3
1	1	1
2	2	2
6	6	6
4	4	4
5	5	5
9	9	9
7	7	7
8	8	8
12	12	12
10	10	10
11	11	11
18	18	18
17	17	17
15	15	15
16	16	16
19	19	19
13	13	13
14	14	14
SHELL	SHELL	SHELL

ELECTRICAL PROPERTIES:

1. 100% OPEN SHORT MIS-WIRE TEST
2. CONTACT RESISTANCE:10Ω
3. INSULATION RESISTANCE:5MΩ
4. HI-PDT:300V /10ms

4	(1P*30#+D+AL+MYLAR)*5C+4C*30#+AL+B UL20276 BLACK IN COLOR 1.4	PCS	1
3	HDMI 19P A MALE SHELL PLATED:GOLD CONTACT:G/F	PCS	1
2	PVC MOLDED BLACK IN COLOR		
1	HDMI 19P FEMALE SHELL PLATED:GOLD CONTACT:G/F	PCS	2
No.	DESCRIPTION	UNIT	Q'TY

REV.	DESCRIPTION	DATE
------	-------------	------

UNLESS OTHERWISE SPECIFIED TOLERANCE		65226
ANG.	±5°	
D.	±0.5	
.0	±0.3	
.00	±0.2	
SCALE:	NONE	UNIT: mm
DRAWN	10/03/29	DRAWN NAME:
CHECKED	/ /	
APPROVED	/ /	PRODUCT NO.
		FILE NAME: