

# Connector Multiport female eSATAp + USB 3.0

## Description

This connector by Delock can be soldered on your PCB. The Multiport is a combination of eSATA and USB 3.0 interface, which supports a fast data transfer and a voltage supply of up to 5 V. The Multiport interface supports up to four connecting options:

1. USB 3.0 (Power via USB)
2. USB 2.0 (Power via USB)
3. eSATAp (Power Over eSATA combo-connection eSATA+USB - eSATA for data and USB for power)
4. eSATA (eSATA for data and power via USB)

## Images



Ref.	65285
EAN	4043619652853
Country of origin	Taiwan
Customs tariff number	84718000

## Specification

- Connector: eSATAp + USB 3.0 female > 16 pin DIP type
- THT PCB assembly
- Solder pin 1-4 (USB 2.0): Ø 0.92 mm
- Solder pin 5-11 (eSATA): Ø 0.75 mm, pitch: 1.27 mm
- Solder pin 12-16 (USB 3.0): Ø 0.92 mm, pitch: 2.25 mm
- Housing material: thermoplastic high temp UL 94-V0
- Operating temperature: -40 to +85 °C
- Contact area (eSATAp + USB): gold-plated
- Dimension (LxWxH): 18.39 mm x 20.42 mm 7.7 mm

### System requirement

- PCB with eSATAp + USB 3.0 through holes

### Package content

- Connector

### Package

- Delock poly bag