RoHS

NOTES:
1.MATERIAL:
HOUSING:THERMOPLASTIC, HIGH TEMP, 30% G/F UL94 V-0
COLOR:BLACK
SHELL:STAINLESS STEEL
ESATA CONTACT:COPPER ALLOY
USB2.0 CONTACT:COPPER ALLOY
USB3.0 CONTACT:COPPER ALLOY
2.FINISH:
CONTACT:GOLD PLATING ON CONTACT AREA
100u" MIN. TIN PLATING ON SOLDERTAILS
50u" MIN. NICKEL UNDERPLATING OVER ALL
SHELL: 50u" MIN.NICKEL UNDERPLATING OVERALL









RECOMMEND P.C.BOARD LAYOUT T=1.20mm
PCB TOLERANCE:±0.05



PIN DEFINITION

USB3.0	
NAME	TYPE
P12	SSRX-
P13	SSRX+
P14	GND
P15	SSTX-
P16	SSTX+

USB2.0	
NAME	TYPE
P1	VBUS
P2	D-
P3	D+
P4	GND

ESATA	
NAME	TYPE
P5	GND
P6	A+
P7	A-
P8	GND
P9	B-
P10	B+
P11	GND

1	UPDATE DRAWING		AW / AW	01SETP 2010
0	FIRST RELEASED	-	PF / AW	12MAY 2010
LTR	REVISION RECORD	ECN	DWN / CHK	DATE

TOLERANCES UNLESS OTHERWISE SPECIFIED
0 PLC ±-
1 PLC ±0.38
2 PLC ±0.25
3 PLC ±0.13
ANGLES ±3°

MATERIAL
SEE NOTE

FINISH
SEE NOTE

DELOCK® we move the world

Item no. 65285

Barcode: 4043619652853

File: 87743

CUSTOMER DRAWING

METRIC
3RD ANGLE PROJECTION
NUMBER
DIMENSIONS IN MILLIMETERS. DO NOT SCALE PRINT.
PRINT DIST DW

D C B A

8 7 6 5 4 3 2 1