





ELECTRICAL PROPERTIES:

1. 100% OPEN SHORT MIS-WIRE TEST
2. Contact Resistance:10ohm
3. Insulation Resistance:5Mega ohm
4. Hipot test:300V/10ms.

Pin assignemnt

USB3.0 AF(1) H20P			USB3.0 AF(2) H20P		
1	1	28AWG RED(PWR)	1	12	28AWG RED(PWR)
2	8	28AWG WHITE(UTP_D-)	2	19	28AWG WHITE(UTP_D-)
3	9	28AWG GREEN(UTP_D+)	3	20	28AWG GREEN(UTP_D+)
4	7	28AWG BLACK(GND_PWRrt)	4	18	28AWG BLACK(GND_PWRrt)
5	2	28AWG YELLOW(SDP1-)	5	13	28AWG YELLOW(SDP1-)
6	3	28AWG BLUE(SDP1+)	6	14	28AWG BLUE(SDP1+)
7	4	28AWG DRAIN(SDP1_Drain) (SDP2_Drain)	7	15	28AWG DRAIN(SDP1_Drain) (SDP2_Drain)
8	5	28AWG ORANGE(SDP2-)	8	16	28AWG ORANGE(SDP2-)
9	6	28AWG PURPLE(SDP2+)	9	17	28AWG PURPLE(SDP2+)
SHELL	10	Braid	SHELL	10	Braid

NO.	DESCRIPTION	Q'TY	UNIT
4	55P PVC MOLDING COLOR:BLUE	1	pcs
3	USB3.0 A TYPE FEMALE SHELL PLATED:NICKEL CONTACT:15U"	2	pcs
2	HOUSING PH2.0MM 2*10P BLUE	1	pcs
1	UL20276 (1P*28#+D+AL+Mya1r)*2C+1P*28#+2C*28#+AL+B OD:5.5±0.15mm BLUE IN COLOR	2	pcs

REV.	DESCRIPTION	DATE
A		11/03/15

UNLESS OTHERWISE SPECIFIED TOLERANCE
ANG. ±5°
0. ±0.5
.0 ±0.3
.00 ±0.2

SCALE:		UNIT: mm
DRAWN	YaoKui	11/03/15
CHECKED	Eric	11/03/15
APPROVED		
SIZE A4	REV. A	

DELOCK® we move the world

Item no. 82941

Description: Cable USB 3.0 Pinheader 2x USB 3.0 A-female 45 cm side by side

Barcode: 4043619829415

File: 87715