

Delock industry mini PCI Express WLAN PCIe full size 2T2R 300 Mb/s

Description

The Delock mini PCI Express module offers in a compact construction WLAN function via mini PCI Express interface and is ideal for installation in industry components like sensor, IPCs, PDA or notebook.



Images



Ref.	95895
EAN	4043619958955
Country of origin	China
Customs tariff number	85176990

Specification

- Mini PCI Express – full size
- Chipset: Ralink RT3092 MAC/BBP/Transceiver
- WLAN IEEE 802.11 b/g/n up to 300 Mb/s
- Frequency band: 2.4 GHz
- Supports WEP 64/128, WPA, TKIP, AES
- Supports QoS-WMM, WMM-PS and Multiple BSSID
- Supports Cisco CCX up to V 5.0
- 2 x antenna connection SMT mini Coax (I-PEX)
- Voltage: 3,3 V +/- 0,3 %
- Operating temperature: 0 °C ~ 65 °C
- Relative humidity: 95 % (non-condensing)
- PCI Express 1.1 specification
- Dimension (LxWxH): 50.8 mm x 29.85 mm x 3.92 mm

System requirement

- A free Mini PCI Express Slot
- Windows 2000/XP/XP-64/Vista/Vista-64/7/7-64, Win CE 5.0/6.0, Linux 2.6x, Mac OS

Package content

- WLAN mini PCI Express module
- Driver CD

Package

- Delock antistatic bag