



REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	CHKD
02				

NOTES:

ELECTRICAL:

- 1.VOLTAGE RATING : 125 VAC RMS
- 2.CURRENT RATING : 1.5 AMP
- 3.CONTACT RESISTANCE : 100 MILLIOHMS MAX
- 4.INSULATION RESISTANCE : 1000 MEGOHMS MIN @ 500 VDC
- 5.DIELECTRIC STRENGTH : 750 VAC RMS 60Hz,1MIN

ENVIRONMENTAL:

- 1.STORAGE : -40° TO +85°
 - 2.OPERATION : 0° TO 70°
- CONFORM TO ANSI/TIA/EIA 568B CATEGORY 3

MECHANICAL:

1. HOUSING MATERIAL : PC UL94V-0
2. INSERT MATERIAL : FLAME RETARDANCY ABS UL94V-0
3. PCB MATERIAL : FR-4 THICKNESS:1.6mm
4. CONTACT MATERIAL : PHOSPHOR BRONZE STAMP PIN T=0.35mm
5. IDC CONTACT MATERIAL : PHOSPHOR BRONZE T=0.50mm WITH NICKEL PLATING
6. WIRE : AWG 14~26

DELOCK
we move the world

86190		TITLE	
Cot.3 Keystone Jack		DRAWING NO.	
A3		SHEET	
DO NOT SCALE DRAWING		SHEET	