

Specification

96378

Delock USB 2.0 camera 2.1 Mpix

EAN: 4043619963782



Specification

96378

Delock USB 2.0 camera 2.1 Mpix

EAN: 4043619963782

General Description

This is 2.1 mega pixel and fix focus camera with sensor on board, metal housing, lens module and USB2.0 video/image process controller. It is designed for all kinds of electronic image processing.

The HM2131, is a low voltage, high performance, 1/2.7 inch CMOS image sensor that provides the full functionality of a single chip camera using OmniBSI™ backside illumination architecture in a small footprint package. It provides full-frame, sub-sample, windowed or arbitrarily scaled 8-bit/10-bit images in various formats via the control of the Serial Camera Control Bus (SCCB) interface.

Features

- USB specification compliance
 - USB 2.0 and USB 1.1 compliance
 - USB video V1.1 compliance (UVC)
 - USB high speed, full speed auto switching
- Framerates:
 - 30 fps @ 1920 x 1080, 1280 x 800, 1280 x 720, 1024 x 768, 840 x 480, 800 x 600, 640 x 360, 640 x 480, 352 x 288
 - 20 fps @ 848 x 480, 800 x 600
 - 10 fps @ 1280 x 800, 1280 x 720, 1024 x 768
- USB Video Class compliant, works with native driver in Microsoft Windows XP 32-bit/64-bit, VISTA 32-bit/64-bit, Windows 7/8/10 system, also with Linux with UVC Video4Linux
- Auto Exposure (AE).
- Auto White Balance (AWB)
- Auto Flicker Correction.
- Color Correction.
- Gamma Correction.
- Dark Level Compensation.
- Auto Edge enhancement.
- Software controlled connection to USB bus for re-enumeration.
- Adjustable and dynamic frame rate control on USB transaction.
- Automatic frame rate adjustment when exposure in low light environment.
- Selective suspend to minimize power consumption.

Specification

96378

Delock USB 2.0 camera 2.1 Mpix

EAN: 4043619963782

Character:

- Total height: 23.50 mm +/- 0.10 mm
- With IR filter
- Working temperature: 0°C ~ 60°C
- Storage temperature: -30°C ~ 70°C

Parameter	SPEC.
Optical sensor	HM2131, 1/2.7 inch CMOS
Sensor resolution	1920 (H) x 1080 (V)
Unit pixel size	3 µm
Image area	5784 µm x 3264 µm
Color filter	RGB Bayer pattem
Shutter type	Electronic rolling shutter
Max. video frame rate	30 fps
F Number	2.7
AEC / AGC/ white balance	Auto
Focus distance	Fix focus 0,05 m - 100 m
Interface	USB 2.0
Power	USB Bus Power
Dimensions (mm) (LxWxH)	ca. 35.8 x 35.8 x 23.5
Operating temperature	0°C ~ 60°C
Operating system request	Windows 7/7-64/8.1/8.1-64/10/10-64
Max pixel rate	28 Mp/s
ADC accuracy	10-bit
USB 2.0 PHY	On Chip PHY
Power consumption VGA	ca. 150 mA
1080p	ca. 180 mA

Specification

96378

Delock USB 2.0 camera 2.1 Mpix

EAN: 4043619963782

Video capability


Standard	Resolution	fps
HVGA	352x288	30 fps
VGA	640x480	30 fps
XGA	640x360	30 fps
720p	800x600	30 fps
	840x480	30 fps
	1024x768	30 fps
1080p	1280x720	30 fps
	1280x800	30 fps
	1920x1080	30 fps

System requirements

- Device with Microsoft Windows 7/7-64/8.1/8.1-64/10/10-64 or Linux above kernel 2.6.15 with Video4Linux

Optical lens specification

	Field of view	F
96378	D=125° / H=100° / V=64°	2.7



Specification

96378

Delock USB 2.0 camera 2.1 Mpix

EAN: 4043619963782

WEEE note

The WEEE (Waste Electrical and Electronic Equipment) directive, which came into force on 13 February 2003, lead to a comprehensive change in the disposal of used electric products. It is the main purpose of this directive to avoid electric waste products (WEEE), while simultaneously promoting the re-usage, recycling and other forms of reconditioning in order to reduce the amount of waste. The WEEE logo on the product and the package shows that the product should not be disposed of with regular garbage. You are responsible for disposing all used electric and electronic devices at the corresponding collection sites. The separate collection and meaningful re-usage of electronic waste helps to deal with natural resources more economically. In addition, re-using electronic waste contributes to the preservation of the environment and human health. Additional information regarding the disposal of electric and electronic devices, their re-usage and the collection sites can be found at your local authorities, disposal companies, specialist shops and the manufacturer of the product.

RoHS conformity

This product complies with the directive 2002/95/EC of the European parliament and the council from January 27th 2003 concerning the restricted use of dangerous substances in electrical and electronical devices (RoHS) as well as its modification. This product is compliant with Directive 2011/65/EU of 3 January 2013.

Specification

96378

Delock USB 2.0 camera 2.1 Mpix

EAN: 4043619963782

Support Delock

If you have further questions, please contact our customer support
support@delock.de.

You can find current product information on our homepage: www.delock.com.

Final clause

Information and data contained in this manual are subject to change without notice in advance. Errors and misprints excepted.

Copyright

No part of this user manual may be reproduced, or transmitted for any purpose, regardless in which way or by which means, electronically or mechanically, without explicit written approval of Delock.

Edition: 10/2018

EU Import: Tragant Handels- und Beteiligungs GmbH
Beeskowdamm 13/15, 14167 Berlin, Germany