




NOTE:

Display port 1.2 Mode
Input: Display port Male Source
Output: Display port Male Display
Plug and Play
Connector the pin and shell gold plating
metal housing with lock
Converts electrical data signals to optical signals
4core OM3 Multimode Fiber (high speed data)and 7core copper cable
Round cable Black TPU jacket OD:4.8mm
Easy to install with Active Optic Cable



Laser Sculpture at Display End: CE and WEEE



Laser Sculpture at Source End: LOGO



3D/HDCP2.2/EDID

MATERIAL LIST:

NO.	PARTS. NAME	SPECIFICATION STANDARD	QT'Y
⑤	dust cap	transparent pe	2
④	BOOT	TPU BLACK	2
③	SHELL	Zinc alloy BLACK	1
②	DP CONNECTOR	DP 20P/M WTIH LATCHING SOLDER TYPE, BLACK INSULATION, GOLD PLATED PIN,GOLD PLATED SHELL,WITH LOCK	1
①	CABLE	{4*OM3+LSZH}+28AWG BC*3C+26AWG BC*2C+(30AWG BC+E+AL)*1P TPU Jacket OD:4.8mm black	1

DELOCK
we move the world

Date	2019 / 09 / 02	Title:	Active Optical DisplayPort Cable
Unit	mm	Item no.	85520
Projection		Barcode	4043619855209
Rev	A	File No.	