


Specification

95865

Delock industry Bluetooth 2.1 EDR USB 2.0 module (mini. Coax)



date: 28.04.2009

Specification

95865

Delock industry Bluetooth 2.1 EDR USB 2.0 module (mini. Coax)

Contents:

- device overall description
- Bluetooth
 - features
 - specification compliance
 - Bluetooth block diagram
 - modulation methods
 - channel assignment
 - RF characteristics
 - antenna connector
 - host interface connector
 - power consumption
 - software & OS support
 - regulation
- mechanical dimension
- pinout and definition

Specification

95865

Delock industry Bluetooth 2.1 EDR USB 2.0 module (mini. Coax)

• Device Overall Description

The 95865 is designed to provide Bluetooth 2.1 + EDR function on a small form factor. The Bluetooth function is based on CSR BlueCore4-ROM (A07) Single Chip Bluetooth System, which implements the full speed class 2 Bluetooth operations with full 7 slave Piconet support. The interface of 95865 to host system is USB and full compliant with USB V1.1 and compatible with USB V2.0 Full Speed (12Mbps/s).

• Bluetooth

Features

- CSR BlueCore4-ROM (A07) Single Chip Bluetooth System
- Bluetooth 2.1 + EDR support
- Class 2 Bluetooth operation with full 7 slave Piconet support
- Full Speed USB interface compliant with USB V1.1 and compatible with USB V2.0
- Single onboard Antenna connector support
- Simple Pairing, Version 2.1 + EDR to advance its short range wireless technology and make it easier for consumers to connect *Bluetooth* devices.

Specification Compliance


- Bluetooth Specification V1.2, V2.0, V2.1 and V2.1+EDR compliant
- USB Specification V1.1
- compatible with USB V2.0 Full Speed (12Mbps/s)

Specification

95865

Delock industry Bluetooth 2.1 EDR USB 2.0 module (mini. Coax)

Bluetooth Block Diagram



Specification

95865

Delock industry Bluetooth 2.1 EDR USB 2.0 module (mini. Coax)

Modulation methods

FHSS (frequency hopping spread spectrum) defined in Bluetooth specification.

	Data rate	Modulation scheme
Basic data rate	1 Mbps	GFSK
Enhanced data rate	2 Mbps	$\pi/4$ DQPSK
	3 Mbps	8DQPSK

Channel assignment

Country	Freq. range	RF channel
Europe* & USA	2400~2483.5MHz	Freq. = 2402 + k MHz k = 0~78
Japan	2400~2483.5MHz	Freq. = 2402 + k MHz k = 0~78

*Most Europe area except Spain and France

Bluetooth power consumption

Electrical characteristics	Minimum	Typical	Maximum	Units
Supply voltage	3	3,3	3,6	V
Continuous RX supply current		55		mA
Continuous TX supply current		46		mA
Idle mode		3,3 ~ 9		mA
Radio disable mode		0,07		mA

Specification

95865

Delock industry Bluetooth 2.1 EDR USB 2.0 module (mini. Coax)

RF Characteristics

RF Characteristics	Mini.	Typical	Max.	SPEC Requirement	Units
Antenna I/F Impedance		50			ohms
Ambient Operating Temperature Range	0		70		°C
Storage Temperature Range	-20		85		°C
Supply Voltage (3.3V only)	3	3	3,6		V
TX Supply Current (at 3.3V)		55			mA
RX Supply Current (at 3.3V)		46			mA
Idle mode Current		3,3 ~ 9			mA
Basic Rate RX Sensitivity, 2402 Mhz		< -70		-70	dBm
Basic Rate RX Sensitivity, 2441 MHz		< -70		-70	dBm
Basic Rate RX Sensitivity, 2480 MHz		< -70		-70	dBm
EDR RX Sensitivity, 2402 MHz		< -70		-70	dBm
EDR RX Sensitivity, 2441 MHz		< -70		-70	dBm
EDR RX Sensitivity, 2480 MHz		< -70		-70	dBm
TX Output Power, 2402MHz		2		-6 ~ +4	dBm
TX Output Power, 2441MHz		2		-6 ~ +4	dBm
TX Output Power, 2480MHz		2		-6 ~ +4	dBm
Initial Carrier Frequency Tolerance	>-10		<10	+/-75	khz
Carrier Frequency Drift, DH3 (01010101)	>-10		<10	40	khz
Carrier Frequency Drift, DH5 (01010101)	>-10		<10	40	khz
Carrier Frequency Drift Rate, DH3 (01010101)	>-10		<10	20	khz
Carrier Frequency Drift Rate, DH5 (01010101)	>-10		<10	20	khz
Modulation Characteristics, Δf1 avg (DH1 ,00001111, kHz)		165		140~175	khz
Modulation Characteristics, Δf2 max (DH1 ,00001111, kHz)		180		>115	khz
Modulation Characteristics, Δf2 avg / Δf1 avg		1		>=0,8	khz
20 dB Bandwidth			>900	1000	khz
TX Output Spectrum – Frequency Range (FL)	2401			2400	Mhz
TX Output Spectrum – Frequency Range (FH)			2481	2483,5	Mhz
Maximum Input Level		>-20		-20	dBm
EDR Maximum Input Level		>-20		-20	dBm

Specification

95865

Delock industry Bluetooth 2.1 EDR USB 2.0 module (mini. Coax)

Host Interface Connector

Connector:

1. Kabo Wafer-1.0-1001-1093
2. ACES 87213-1000
3. or compliance

Software & OS support:

- Windows Vista/XP SP2 native supported Profiles - DUN, HCRP, HID, OPP, PAN-U and SPP
- IVT Bluesoleil Bluetooth Stack for **Windows Vista/XP** –A2DP, AG, AV, BIP, DUN, FTP, HCRP, HID, LAP, OPP, PAN-GN, PAN-U, SPP, SYNC and HS.
(Profiles might change without prior notice; please refer to the SW release document for detail.)

IVT Bluesoleil Bluetooth Stack for Windows Vista/XP, Bluetooth SIG QDID B010568

Regulation:

QBTM400 : Bluetooth SIG QD ID B013757


Specification

95865


Delock industry Bluetooth 2.1 EDR USB 2.0 module (mini. Coax)

• Mechanical dimension

- 28mm x 14mm x 3.9mm (L x W x H) +- 0.15mm
(additional barcode label thickness: 0.14mm +/-0.01mm)



- Component height (unit: mm)



Specification

95865

Delock industry Bluetooth 2.1 EDR USB 2.0 module (mini. Coax)

Pinout and definition

Pin#	signal name	description
1	GND	
2	USB D+	USB data plus
3	USB D-	USB data minus
4	reserved	
5	BT_Active	For WLAN & BT co-existence signal
6	BT_On	Active High to enable BT function, low to disable BT function
7	WLAN_Active	For WLAN & BT co-existence signal
8	+3,3V	Positive supply for whole module
9	LED	BT activity LED indicator, active high to indicate the BT activity.
10	GND	

cable optional Delock A95845

