

Wall Socket with 2 x USB Type-A Charging Port 2.4 A

Description

This power socket with a side grounding contact by Delock is for installation in a standard flush-mounted or cavity installation box. In addition to a CEE 7/3 socket with childproof lock, this power socket side grounding contact offers two USB Type-A charging ports. Thus, smartphones, tablets and similar devices can be charged while the socket is still available.



Item no. 11471

EAN: 4043619114719

Country of origin: China

Package: Box

Technical details

- Connectors:
 - 1 x power socket CEE 7/3 with childproof lock
 - 2 x USB Type-A charging port max. 2.4 A
 - 3 x screw terminal for PE, N, L
- Robust plastic housing
- Rated current socket CEE 7/3: 16.0 A / 250 V~
- Rated power socket CEE 7/3: 4000.0 W
- USB Charger:
 - Short circuit protection
 - Input current: 0.2 A
 - Output voltage / Output current / Output power:
 - USB Type-A 5.0 V / 2.4 A (max. 12.0 W)
 - Average active efficiency: 82.2 %
 - Efficiency at low load (10 %): 74.5 %
 - No-load power consumption: 0.05 W
 - Suitable for standard installation box
 - Colour: white
 - Dimensions (LxWxH): ca. 80 x 80 x 53 mm

System requirements

- Mains supply with grounding
- A free standard installation box

Package content

- Power socket
- User manual

Images



General

Mounting type:	in-wall
Protection:	Input overvoltage protection Short circuit protection

Interface

Connector 1:	1 x 3 pin terminal block screw terminal
Connector 2:	1 x power socket CEE 7/3 with childproof lock
Connector 3:	2 x USB Type-A female

Physical characteristics

Length:	80 mm
Width:	80.0 mm
Height:	56 mm
Colour:	white

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

