

# Delock WLAN 802.11 b/g/n Antenna RP-SMA plug 2 dBi omnidirectional with tilt joint white

## Description

This Wireless LAN antenna can be connected to a WLAN device with RP-SMA interface, in order to send and receive signals.



**Item no. 12006**

EAN: 4043619120062

Country of origin: Taiwan,  
Republic of China

Package: Zip poly bag

## Specification

- Connectors: 1 x RP-SMA plug
- Frequency range: 2.400 - 2.500 GHz
- Antenna gain: 2 dBi
- Impedance: 50 Ohm
- VSWR: 2.0
- Polarisation: linear, vertical
- Operating temperature: -45 °C ~ 85 °C
- Colour: white
- Length:
  - ca. 108.00 mm (with tilt joint)
  - ca. 82.50 mm (without tilt joint)
- Diameter:
  - ca. 7.80 mm (top)
  - ca. 10.00 mm (RP-SMA)

## System requirements

- Device with a free RP-SMA jack
- 

## Package content

- WLAN antenna
- 

## Images



## General

Suitable for indoor:	yes
----------------------	-----

## Interface

connector:	1 x RP-SMA plug
------------	-----------------

## Technical characteristics

Antenna gain:	2 dBi
Impedance:	50 Ohm
Polarisation:	linear vertical
VSWR:	2.0

## Physical characteristics

Antenna type:	dipol antenna omnidirectional
Housing material:	PC PBT
Diameter:	7.8 mm
Diameter connector:	10.0 mm
Length with tilt joint:	108.0 mm
Length without tilt joint:	82.5 mm
Colour:	white