

# Delock Antenna Cable N plug > RP-SMA plug CFD400 LLC400 10 m low loss

### Description

This high-quality coaxial cable ensures a reliable connection of components of the radio frequency technology. It is characterised by a **very low attenuation**. Thanks to the **waterproof** N connector, this cable is ideal for outdoor use.



#### Item no. 13028

EAN: 4043619130283 Country of origin: Taiwan, Republic of China Package: Box

### Specification

- Connectors:
   1 x N plug waterproof >
   1 x RP-SMA plug
- Impedance: 50 Ohm
- Cable type: CFD400, LLC400
- Cable type: coaxial
- Cable attenuation:
  0.3 dB @ 3.0 GHz per meter
  0.48 dB @ 6.0 GHz per meter
- Cable diameter: ca. 10.5 mm
- Smallest bending radius: 51.5 mm
- Cable colour: black
- Length incl. connectors (L): ca. 10 m

### System requirements

• Device with one free N and RP-SMA port





## Package content

• Antenna cable

### Images



	1		O MAR	1047 U	200		. 6	500.000		1.04	
2	2		40 ON	1.0\$3 U	1.1		2		00 GHz	1.06	
	12		के के	T.52 U		_	-1	2,000		1.13	
			40.04	1.58 U					00 094	111	
7	- 6		to ale	108 0			-6-	40000		104	
<u>i</u>	1		40.04	120 U	- é-	_	4		00.082	123	
5	7	epoor	10 014	1.585 U	- 6-	-	7	4,0000	00 012	1.42	-
-				6	E.	_				6	-
1-2-		-		10000	+ - z-	*	•	-		1.	
		We -10 d	Den Delli Cel	Stop 6 GHz	Chi s	Start 916	a.	Per -10 dB	in	Stop	19
4 🚮 (0)					Chi s	Start 916	a.	Per -10-da			
4 🚮 d01					CH S		a l		D MHz	Stop (	6
4 🚮 d01					CM S	1	a l	500.000	0 MHz	1.098	0
4 🚮 d01 🕅					CHI S	1	ùr.	500.0000	0 MHg 0 MHg 0 Hg 0 Hg	1.098	6 6 6
					CM S	1	a .	500-0000 1.00000 2.00000	0 MH12 0 09-12 0 09-12 0 09-12	1.098	00000
					CH S	2	a	502.0000 1.00000 2.00000 9.00000 4.00000 5.00000	0 MH2 0 GH2 0 GH2 0 GH2 0 GH2 0 GH2 0 GH2 0 GH2	1.098 1.588 0.272 0.961 0.411 0.745	222223
4 53 dB1					CH 1	1	ir .	502-0000 1.00000 2.00000 9.00000 4.00000	0 MH2 0 GH2 0 GH2 0 GH2 0 GH2 0 GH2 0 GH2 0 GH2	1.098	222223
4 33 d01					CH 1	1 2 3 4 5 6 7	5	502.0000 1.00000 2.00000 9.00000 4.00000 5.00000	0 MH2 0 GH2 0 GH2 0 GH2 0 GH2 0 GH2 0 GH2 0 GH2	1.098 1.588 0.272 0.961 0.411 0.745	222223
					CH 1	1 2 3 4 5 6 7		502.0000 1.00000 2.00000 9.00000 4.00000 5.00000	0 MH2 0 04 0 04 0 04 0 04 0 04 0 04 0 04 0 0	1.098 1.588 0.272 0.961 0.411 0.745	222223





#### Interface

Connector 1:	1 x RP-SMA plug
Connector 2:	1 x N male

### **Technical characteristics**

	Impedance:	50 Ω
--	------------	------

### **Physical characteristics**

Cable type:	CFD400, LLC400
Cable attenuation:	0.30 dB @ 3.0 GHz 0.48 dB @ 6.0 GHz
Cable colour:	black
Cable length:	10 m
Smallest bending radius:	51.5 mm