


# Delock Adapter M.2 Key B+M male to CFexpress Slot

## Description

This adapter by Delock can be used to connect a **CFexpress memory card** to the **M.2 interface**. Through the predetermined breaking point, the length can be shortened from 80 mm to 60 mm.



**Item no. 21360**

EAN: 4043619213603

Country of origin: Taiwan,  
Republic of China

Package: Retail Box

## Specification

- Connectors:
  - 1 x M.2 key B+M male
  - 1 x CFexpress 2.0 slot type B
- Interface: PCIe Rev. 3.0
- Form factor: 2280 or 2260
- Suitable for M.2 slot with key M or B based on PCIe
- Push to push CFexpress socket
- Supports NVM Express (NVMe)
- LED indicator for power
- Bootable, ex UEFI version 2.3.1
- Dimensions (LxWxH): ca. 80 x 37 x 5 mm

## System requirements

- Linux Kernel 3.17 or above
- Windows 8.1/8.1-64/10/10-64/11
- A free M.2 key M or key B slot

## Package content

- Adapter
- User manual

## Images



## General

Form factor:	M.2 2280
Function:	Bootable, ex UEFI 2.3.1
Supported operating system:	Linux Kernel 3.17 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows 11
LED indicator:	power and activity
Supported memory card:	CFexpress

## Interface

Connector 1:	1 x M.2 key B+M male
Connector 2:	1 x CFexpress slot