

Push Button for Installation 12 mm 2 x Screw Terminal white

Description

This push button by Delock is ideal for installation in control panels, for example in industry, control or regulation technology. Push buttons can also be found in the automotive industry or the consumer sector. For example, as doorbells or triggers for lighting systems with timers such as those found in hallways.

Button

A so called button, or push button, returns to its initial position after being pressed.

Opener and closer

The NO (closer) contact establishes a connection between two contacts, while the NC (opener) contact releases them.



Item no. 22035

EAN: 4043619220359

Country of origin: China

Package: Zip poly bag

Technical details

- Connectors: 2 x screw terminal
- Switch type: 1 closer (NO)
- Load limit: AC 250 V~ / 3 A
- Number of contacts: 2
- Number of open contact: 1
- Function: momentary
- Actuator: domed
- Operating temperature: -25 °C ~ 55 °C
- Mounting hole diameter: ca. 12 mm
- Hexagon nut spanner width: 14 mm
- Mounting depth: ca. 15 mm
- Thread size: M12
- Colour of push button: white
- Material: stainless steel nickel plated
- Mechanical life: 1,000,000 cycles
- Electrical service life: 100,000 cycles
- Protection class: IP65
- Dimensions (LxD): ca. 22.0 x 17.5 mm

Package content

- Push-button

Images



General

Mounting type:	Screw mounting
Protection class:	IP65
Style:	momentary

Technical characteristics

Load limit:	AC 250 V~ / 3 A
Operating temperature:	-25 °C ~ 55 °C

Physical characteristics

Housing material:	stainless steel nickel plated
Colour:	white silver
Thread type:	M12
Mounting hole diameter:	12 mm

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de