

# Push Button for Installation 22 mm 5 x solder connection actuator flat plastic LED green

## Description

This push button by Delock is ideal for installation in control panels, for example in industry, control or regulation technology. Push buttons can also be found in the automotive industry or the consumer sector. For example, as doorbells or triggers for lighting systems with timers such as those found in hallways.

A so called button, or push button, returns to its initial position after being pressed.

The NO (closer) contact establishes a connection between two contacts, while the NC (opener) contact releases them.



**Item no. 22048**

EAN: 4043619220489

Country of origin: China

Package: Zip poly bag

## Technical details


- Connectors: 5 x solder connection
- Switch type: 1 closer (NO) + 1 opener (NC)
- Load limit: AC 230 V~ / 3 A
- Number of contacts: 5
- Number of LED: 2
- Function: momentary
- Actuator: flat
- Operating temperature: -25 °C ~ 55 °C
- Mounting hole diameter: ca. 22 mm
- Mounting depth: ca. 40 mm
- Thread size: M16
- LED lighting: green
- LED voltage: 12 V
- Material: plastic
- Mechanical life: 1,000,000 cycles
- Electrical service life: 100,000 cycles
- Protection class: IP60
- Dimensions (LxD): ca. 41 x 22 mm

## Package content

- Push-button

---

## Images



### General

Mounting type:	Soldering
Protection class:	IP60
Style:	momentary

### Technical characteristics

Load limit:	AC 250 V~ / 2 A
Operating temperature:	-25 °C ~ 55 °C

### Physical characteristics

Housing material:	Plastic
Colour:	black
Thread type:	M16
LED colour:	green

### Manufacturer information

Street                    Beeskowdamm 13/15  
 Postal code            14167  
 City                      Berlin  
 Country                Deutschland  
 E-Mail                  info@delock.de  
 Website                www.delock.de

