

# Delock Riser Card PCI Express x1 > x16 with 60 cm USB cable

#### Description

The PCI Express riser card by Delock can be plugged into any PCI Express x1 slot on the motherboard. Then the x16 PCI Express slot can be mounted in a different position in the case. This allows a graphics card to be operated in each PCIe slot of a motherboard, even if the graphics card is wider than a single slot. By using several riser cards, several graphics cards can be operated simultaneously on one motherboard, e.g. for mining crypto currencies such as Bitcoin, Ethereum or Zcash.



#### Item no. 41426

EAN: 4043619414260 Country of origin: China Package: Retail Box

#### Note

The package content includes a USB 3.0 riser cable with a length of 60 cm. No USB signals are transmitted through this cable, therefore it is not possible to exchange it with a different or longer cable.

#### Special features

A PCle x16 graphics card can be used with a PCle x1 slot.

### **Specification**

· Connectors:

Motherboard side:

1 x PCI Express x1

1 x USB 3.0 Type-A female

Riser side:

1 x PCI Express x16

1 x USB 3.0 Type-A female

1 x 6 pin PCIe power female

- Data transfer rate up to 800 MB/s
- 4 x FP solid capacitors, ensures secure power supply of the graphics card
- 4 x mounting holes on the riser card
- Bottom side with isolating, antislip pad



- · Cable data:
  - 1 x riser cable USB 3.0 Type-A male to male ca. 60 cm (incl. connectors)
  - 1 x power cable 6 pin to SATA ca. 20 cm (incl. connectors)
- Dimensions of the riser card (LxWxH): ca. 128.25 x 43.50 x 21.20 mm
- OS independent, no driver installation necessary

### System requirements

- PC with one free PCI Express x1 / x4 / x8 / x16 / x32 slot
- · Power supply with a free SATA power connector

## Package content

- PCle to USB riser card
- USB to PCIe riser card
- USB 3.0 cable
- Power cable

### **Images**









#### General

Supported operating system: OS independent, no driver installation necessary	
--	--

## **Technical characteristics**

Data transfer rate: up to 800 MB/s

# **Physical characteristics**

Length:	128.25 mm
Width:	43.50 mm
Height:	21.20 mm