

Delock Riser Card PCI Express x1 to x16 with 60 cm USB cable

Description

The PCI Express riser card by Delock can be plugged into any PCI Express x1 slot on the motherboard. Then the x16 PCI Express slot can be mounted in a different position in the case. This allows a graphics card to be operated in each PCIe slot of a motherboard, even if the graphics card is wider than a single slot. By using several riser cards, **several graphics cards can be operated simultaneously on one motherboard**, e.g. for mining crypto currencies such as Bitcoin, Ethereum or Zcash.

Note

The package content includes a USB 3.0 riser cable with a length of 60 cm. No USB signals are transmitted through this cable, therefore it is not possible to exchange it with a different or longer cable.

Special features

• A PCIe x16 graphics card can be used with a PCIe x1 slot.

Specification

- Connectors: Motherboard side:
 1 x PCI Express x1
 1 x USB 3.0 Type-A female Riser side:
 1 x PCI Express x16
 1 x USB 3.0 Type-A female
 - 1 x Molex 4 pin power connector
- Data transfer rate up to 800 MB/s
- 3 x FP solid capacitors, ensures secure power supply of the graphics card
- 4 x mounting holes on the riser card
- · Bottom side with isolating, antislip pad



EAN: 4043619414307 Country of origin: China Package: Retail Box

DATASHEET



- Cable data:
 - 1 x riser cable USB 3.0 Type-A male to male ca. 60 cm (incl. connectors)
 - 1 x power cable SATA to Molex ca. 20 cm (incl. connectors)
- Dimensions of the riser card (LxWxH): ca. 128.25 x 43.50 x 21.20 mm

System requirements

- PC with one free PCI Express slot
- Power supply with a free SATA power connector

Package content

- PCIe to USB riser card
- USB to PCIe riser card
- USB 3.0 cable
- Power cable
- User manual

Images



DATASHEET



General

Technical characteristics

Physical characteristics

Length:	128.25 mm
Width:	43.50 mm
Height:	21.20 mm