

# USB GaN Charger 1 x USB Type-C™ PD 3.1 with 140 W

## Description

This USB charger by Delock can be used to charge a USB devices. The port is equipped with a USB Type-C™ Power Delivery (PD 3.1), thereby supported devices can be charged with up to 140 watt.

### USB-PD Version 3.1

The USB PD 3.1 specification defines the voltage levels 28, 36 and 48 volts with support for Extended Power Range (EPR) with 5 amps each. Due to a calculated maximum power of 240 W (48 V / 5 A), other device classes can be supplied with power in addition to powerful laptops and desktop PCs. The Delock charger features an output power of 28 V and 5 A.

### GaN technology

The use of GaN (gallium nitride) transistors increases efficiency compared to conventional silicon technology. Even with very compact dimensions a high output power can be achieved.

### Please Note

For the EPR mode (28, 36, 48 V / 5 A), a USB cable with a corresponding E-marker is mandatory. If this E-marker is not available, max. 3 A are transmitted.

Corresponding cables by Delock are optionally available.



**Item no. 41471**

EAN: 4043619414710

Country of origin: China

Package: Retail Box

## Technical details

- Connectors:
  - 1 x USB Type-C™ female
  - 1 x plug CEE 7/16
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 2.0 A
- Output:
  - PD 3.1: 5.0 V / 9.0 V / 12.0 V / 15.0 V / 3.0 A, 20.0 V / 28.0 V / 5.0 A
- Output power: max. 140.0 W total
- Average active efficiency 89.75 %
- Efficiency at low load (10 %) 87.28 %
- No-load power consumption 0.182 W
- USB Power Delivery (PD) 3.1
- Overload protection
- Over current protection
- Overheating protection
- Short circuit protection

- Colour: white
- Dimensions without plug (LxWxH): ca. 113 x 75 x 35 mm

---

## Package content

- USB charger
- USB Type-C™ to USB Type-C™ cable, length ca. 1 m
- User manual

---

## Images



## General

Specification:	USB Power Delivery 3.1
----------------	------------------------

## Physical characteristics

Housing colour:	white
Length:	113 mm
Width:	75 mm
Height:	35 mm

## Power supply

Input voltage:	AC 100 - 240 V / 50 - 60 Hz / 2.0 A
Power supply output:	12.0 V / 3.0 A 15.0 V / 3.0 A 20.0 V / 5.0 A 28,0 V / 5,0 A 5.0 V / 3.0 A 9.0 V / 3.0 A
Power supply connector:	1 x USB Type-C™ female

## Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

