

# Delock External Enclosure M.2 SSD 80 mm > SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female

## Description

The aluminium enclosure by Delock enables the installation of a M.2 SSD in 2280, 2260, 2242 and 2230 format, which can be connected via USB to the PC or laptop.



**M.2**

**Item no. 42574**

EAN: 4043619425747

Country of origin: China

Package: Box

## Specification

- Connector:  
external: 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female  
internal: 1 x 67 pin M.2 key B slot
- Chipset: Asmedia ASM1351
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key B based on SATA
- Maximum height of the components on the module: 1.35 mm application of double-sided assembled modules supported
- Data transfer rate up to 6 Gbps
- LED indicator for power and access
- Dimensions (LxWxH): ca. 126 x 40 x 10 mm
- Hot Plug, Plug & Play

## System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 4.6, Mac OS 10.12
- PC or laptop with a free USB Type-A port

---

## Package content

- External enclosure M.2
- Screwdriver
- Mounting material
- USB 3.1 Type-A to USB-C™ cable (ca. 50 cm)
- User manual

---

## Images



## General

Function:	Hot Plug Plug & Play
Supported operating system:	Linux Kernel 2.6 or above Mac OS 10.8.2 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
Supported module:	M.2 modules in format 2280, 2260 and 2242 with key B or key B+M based on SATA
Maximum height of the components on the module:	1.35 mm application of double-sided assembled modules supported

## Interface

External:	1 x USB 10 Gbps USB Type-C™ female
Internal:	1 x 67 pin M.2 key B slot

## Technical characteristics

Chipset:	Asmedia ASM1351
Data transfer rate:	6 Gb/s

## Physical characteristics

Length:	126 mm
Width:	40 mm
Height:	10 mm
Colour:	black