

# Delock External Enclosure 2 x CFast > USB 3.1 Gen 2 with RAID

## Description

The aluminium enclosure by Delock enables the installation of two CFast memories, which can be connected via USB Type-C™ to the PC or laptop. When using more than one memory card, there is the possibility to use different RAID level.

## Note

The package contains the cable USB-C™ male to USB Type-A male. This can also be used only in this direction. Therefore the USB-C™ male must be connected to the computer and the USB Type-A male to the enclosure.

Optionally there is a cable from Delock USB Type-A male to USB Type-A male (83981), so that this enclosure can also be connected to a computer with USB Type-A interface. In addition, there is the possibility to connect a power supply if the power from the USB port is not enough.



### Item no. 42582

EAN: 4043619425822

Country of origin: Taiwan,  
Republic of China

Package: Retail Box

## Specification

- Connector:
  - external:
    - 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) Type-A female
    - 1 x 5 V DC jack
  - internal:
    - 2 x CFast 2.0 slot
- Chipset: Asmedia ASM1352R
- Supports CFast type I / II memory cards
- Downwards compatible to CFast 1.0
- Supports RAID 0, 1, SPAN, Port Multiplier
- RAID mode set by DIP switch on board
- Data transfer rate up to 10 Gbps
- Enclosure with full-PCB
- Colour: silver
- Dimensions (LxWxH): ca. 136 x 80 x 16 mm

- Hot Plug, Plug & Play

---

## Specification of power connector

- 5 V, ground outside, plus inside
- Dimensions:  
inside:  $\varnothing$  ca. 1.35 mm  
outside:  $\varnothing$  ca. 3.5 mm  
length: ca. 8.5 mm
- Optional power supply: [Navilock 41337](#)

---

## System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 4.6
- PC or laptop with a free USB Type-C™ or Thunderbolt™ 3 port

---

## Package content

- External enclosure
- Cable USB-C™ male to USB Type-A male, length ca. 50 cm
- Cover, screwdriver, screws
- User manual

---

## Images



## General

Function:	Hot Plug Plug & Play
Internal construction:	full PCB
Supported operating system:	Linux Kernel 3.19 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
Supported memory card:	CFast 1.0 and 2.0 CFast type I / II

## Interface

External:	1 x 5 V DC jack 3.5 mm x 1.35 mm 1 x USB 10 Gbps Type-A female
Internal:	2 x CFast 2.0 slot

## Technical characteristics

Chipset:	Asmedia ASM1352R
Data transfer rate:	USB 10 Gbps up to 10 Gb/s
RAID function:	SPAN 0 1 Port Multiplier

## Physical characteristics

Housing material:	Aluminium
Length:	136 mm
Width:	80 mm
Height:	16 mm



Colour:

silver

