

Delock External Enclosure for 3.5" SATA HDD with SuperSpeed USB (USB 3.1 Gen 1)

Description

This plastic enclosure by Delock can be used for the installation of a 3.5" SATA hard drive.

Fast data transfer due to SuperSpeed USB

Due to the JMicron chipset, this hard disk enclosure supports SuperSpeed USB with up to 5 Gbps transfer speed. This allows data to be transferred quickly to and from the hard disk.



Item no. 42612

EAN: 4043619426126 Country of origin: China Package: Retail Box

Specification

- Connectors:
 - external:
 - 1 x SuperSpeed USB (USB 3.1 Gen 1) Type-A female
 - 1 x DC jack
 - internal:
 - 1 x SATA 6 Gb/s 22 pin receptacle
- Suitable for all 3.5" SATA HDDs up to 6 Gb/s
- Chipset: JMicron JMS578
- Data transfer rate:
 - SuperSpeed USB 5 Gbps,
 - Hi-Speed 480 Mbps,
 - Full-Speed 12 Mbps,
 - Low-Speed 1.5 Mbps
- Supports UASP
- On / Off switch
- · LED indicator for power and access
- · Plastic housing
- Colour: black
- Dimensions (LxWxH): ca. 186 x 116 x 35 mm



• Hot Swap, Plug & Play

Power supply specification

• Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.8 A

• Output: 12 V / 2 A

• Ground outside, plus inside

• Dimensions:

inside: ø ca. 2.1 mm outside: ø ca. 5.5 mm length: ca. 11 mm

System requirements

- Linux Kernel 3.3 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- 3.5" external enclosure
- Cable USB Type-A male to Type-A male, length ca. 60 cm
- Power supply
- User manual

Images







PLOCK

we move the world



General

Function:	Plug & Play
Supported operating system:	Android 6.0 or above Chrome OS 72.0 or above Linux Kernel 3.17 or above Mac OS 10.14.3 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

Interface

External:	1 x DC jack 5.5 x 2.1 mm 1 x USB 5 Gbps Type-A female
Internal:	1 x SATA 6 Gb/s 22 pin receptacle

Technical characteristics

Physical characteristics

Housing material:	Plastic
Length:	186 mm
Width:	116 mm
Height:	35 mm
Colour:	black