

# Delock External Enclosure for M.2 NVMe PCIe SSD with USB Type-C™ female transparent

## Description

This enclosure by Delock enables the installation of an **M.2 PCIe NVMe SSD** in 2280, 2260, 2242 and 2230 format, it can be connected via USB to the PC or laptop.

### Transparent enclosure

The **sturdy, transparent plastic housing** provides a view inside to quickly see which memory is inside.

### Note

There is no support for SATA M.2 SSD.



**Item no. 42620**

EAN: 4043619426201

Country of origin: China

Package: Retail Box

## Specification

- Connectors:  
external:  
1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female  
internal:  
1 x 67 pin M.2 key M slot
- Chipset: JMicron JMS583
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on PCIe (NVMe)
- Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
- Supports NVM Express (NVMe)
- Data transfer rate up to 10 Gbps
- LED indicator for power and access
- Transparent plastic housing
- Dimensions (LxWxH): ca. 108 x 34 x 12 mm
- Hot Plug, Plug & Play

## System requirements

- Android 9.0 or above
- Chrome OS 75.0 or above
- Linux Kernel 3.18 or above
- Mac OS 10.14.5 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64/11
- PC or laptop with a free USB Type-C™ port or
- PC or laptop with a free USB Type-A port


---

## Package content

- External enclosure M.2
- Screwdriver
- Mounting material
- Cable USB-C™ male to USB-C™ male (with adapter to USB Type-A male), length ca. 30 cm
- 1 x thermal conductive pad
- User manual

---

## Images



## General

Function:	NVM Express (NVMe) Hot Plug Plug & Play
Internal construction:	full PCB
Supported operating system:	Android 9.0 or above Chrome OS 75.0 or above Linux Kernel 3.18 or above Mac OS 10.14.5 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
Supported module:	M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on PCIe
Maximum height of the components on the module:	1.5 mm application of double-sided assembled modules supported

## Interface

External:	1 x USB 10 Gbps USB Type-C™ female
Internal:	1 x 67 pin M.2 key M slot

## Technical characteristics

Chipset:	JMicron JMS583
Data transfer rate:	up to 10 Gbps

## Physical characteristics

Housing material:	Plastic
Cable length:	50 cm
Length:	108 mm

Width:	34 mm
Height:	12 mm
Colour:	transparent