

# Delock 5.25" Mobile Rack for 4 x 2.5" U.2 NVMe SSD with lockable Trays

## Description

This solid metal mobile rack by Delock can be installed into a free 5.25" bay of a PC, IPC or server enclosure and enables the operation of **up to four 2.5" U.2 SSD**. To ensure the maximum speed at each port, each slot has its own SFF-8643 connector.

### Quick change of SSD

Due to the special mechanism, the SSD can be exchanged quickly and easily. For example, data backups can be taken and stored in a safe place.

### Protection against theft

Each of the four removable frames is provided with a **separate lock**. Thus, the hard disks and data can be protected against theft and misuse.

### Good cooling

In operation, **two 35 mm rear fans** ensure an efficient and effective airflow to cool all 4 slots. The fans can optionally be set to low or high speed to ensure optimal cooling.



**Item no. 47235**

EAN: 4043619472352

Country of origin: Taiwan,  
Republic of China

Package: White Box

## Specification

- Connectors:  
internal: 4 x SFF-8639 female  
external:  
4 x Mini SAS HD SFF-8643 female  
1 x SATA 15 pin power connector
- Suitable for 2.5" U.2 NVMe SSD:  
SSD height up to 15 mm
- Compatible to PCI Express V4.0
- Mobile rack with key lock for each bay
- 4 x LED indicator for power and access
- Robust aluminum housing
- 2 x fan 35 x 35 mm at the back side

- Fan speed control in two steps
- Key lock
- Bootable
- Operating temperature: 0 °C ~ 55 °C
- Storage temperature: -20 °C ~ 55 °C
- Relative humidity: 5 - 65 % (non condensing)
- Dimensions (LxWxH): ca. 146 x 139 x 42 mm

---

## System requirements

- Linux Kernel 5.1 or above
- Windows 8.1/8.1-64/10/10-64
- Windows Server 2016
- A free 5.25" bay
- Up to four free U.2 ports
- Power supply with a free SATA power connector

---

## Package content

- 5.25" mobile rack
- 4 x 2.5" mobile rack inner tray
- 2 x keys
- 8 x rack screws
- 16 x hard drive screws
- User manual

## Images



## General

|                             |                                                                                                                                        |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Form factor:                | 5.25"                                                                                                                                  |
| Suitable for data medium:   | 2.5"<br>height up to 15.0 mm                                                                                                           |
| Supported operating system: | Linux Kernel 5.1 or above<br>Windows 10 32-Bit<br>Windows 10 64-Bit<br>Windows 8.1 32-Bit<br>Windows 8.1 64-Bit<br>Windows Server 2016 |

## Interface

|           |                                                                   |
|-----------|-------------------------------------------------------------------|
| External: | 1 x 15 Pin SATA Stromanschluss<br>4 x Mini SAS HD SFF-8643 female |
| Internal: | 4 x SFF-8639 female                                               |

## Technical characteristics

|                     |         |
|---------------------|---------|
| Data transfer rate: | 32 Gbps |
|---------------------|---------|