

Delock M.2 SSD PCIe / NVMe Key M 2280 - 256 GB

Description

This flash module by Delock is a memory in the M.2 format for the PCIe / NVMe interface. With its 80 mm length, it has the form factor 2280. The module supports PCIe x4 and has the revision 3.0. The high read and write speed supports fast data transfer even for big amount of data, which is particularly important in the photo and video range.



Item no. 54079

EAN: 4043619540792 Country of origin: China Package: Antistatic cover

Technical details

• Connector:

1 x 67 pin M.2 Key M male

· Capacity: 256 GB

• Interface: PCIe x4 Rev. 3.0

Controller: SMI SM2263XT

Maximum read speed: 2000 MB/sMaximum write speed: 1200 MB/s

• Power consumption: max. 2 W

• MTBF: 1.000.000 hours

Flash type: TLC

• Maximum write cycles: 1000

Storage temperature: -55 °C ~ 115 °C
Operating temperature: 0 °C ~ 70 °C

• Shock: 1500G

• Operating vibration: 16G

• Humidity: 5 ~ 98 %

• Supports TRIM

• Supports S.M.A.R.T.

• Supports NVM Express (NVMe) 1.3

• Dimensions (LxWxH): ca. 80.0 x 22.0 x 2.1 mm



System requirements

• A free M.2 key M slot based on PCle

Package content

• M.2 SSD

Images







Interface

connector: 1 x 67 pin M.2 Key M male

Technical characteristics

Storage temperature: -55 °C ~ 115 °C Read: 2000 MB/s Maximum power consumption: 2 W Maximum write cycles: 1000 MTBF: 1.000.000 hours Interface: PCIe x4 Rev. 3.0 Shock: 1500 G Write: 1200 MB/s Capacity: 256 GB Vibration: 16 G **TLC** Flash type:

Physical characteristics

Length:	80.0 mm
Width:	22.0 mm
Height:	2.1 mm