Delock SATA 3 Gb/s Flash Modul 2 GB Vertical / Low Profile

Description

The SATA 3 Gb/s Flash Module is due to its very small size and high shock resistance ideal for application of mobile devices like IPCs, measuring systems as well as Digital Signage etc. Additional snap in will be provided by metal clips on the SATA connectors.



2 GB

N° produit 54368

EAN: 4043619543687

Pays d´origine: Taiwan, Republic of China

Emballage: Antistatic cover

Spécifications techniques

- Capacity: 2 GB
- 7 pin SATA 3 Gb/s interface
- Chip: SLC (Single Level Cell)
- Operating voltage: 5 V +/-5%
- Operating temperature: 0 °C ~ + 70 °C
- Power consumption: read: 230 mA
  write: 330 mA
  idle: 130 mA
- Transfer modes: SATA 3 Gb/s, SATA 1.5 Gb/s, PIO 0~4, MDMA 0~2, UDMA 0~6
- S.M.A.R.T. & i-S.M.A.R.T. supported
- Maximum write cycles: 6000
- Read: up to 30 MB/s; write: up to 25 MB/s
- MTBF: > 3.000.000 hrs
- Vibration: 20G / 7~2000 Hz
- Shock: 1500 G / 0.5 ms
- Dimension: 32.9 x 29.5 x 9.0 mm (LxWxH)

© 2024 by Delock. Tous les noms et images mentionnés ici sont la propriété de leur fabricant respectif.
Sous réserve d’erreurs et de modifications.

Configuration système requise

- A free SATA 7 pin port
- Power supply with a free Molex power connector

Contenu de l’emballage

- 2 GB SATA Flash module
- Power cable

© 2024 by Delock. Tous les noms et images mentionnés ici sont la propriété de leur fabricant respectif.
Sous réserve d’erreurs et de modifications.