

Delock SATA 3 Gb/s Flash Modul 2 GB Vertical / Low Profile

Descrizione

The SATA 3 Gb/s Flash Module is due to its very small size and high shock resistance ideal for application of mobile devices like IPCs, measuring systems as well as Digital Signage etc. Additional snap in will be provided by metal clips on the SATA connectors.



2 GB

Articolo n. 54368

EAN: 4043619543687

Paese di origine: Taiwan,
Republic of China

Pacchetto: Antistatic
cover

Specifiche

- Capacity: 2 GB
- 7 pin SATA 3 Gb/s interface
- Chip: SLC (Single Level Cell)
- Operating voltage: 5 V +/-5%
- Operating temperature: 0 °C ~ + 70 °C
- Power consumption: read: 230 mA
write: 330 mA
idle: 130 mA
- Transfer modes: SATA 3 Gb/s, SATA 1.5 Gb/s, PIO 0~4, MDMA 0~2, UDMA 0~6
- S.M.A.R.T. & i-S.M.A.R.T. supported
- Maximum write cycles: 6000
- Read: up to 30 MB/s; write: up to 25 MB/s
- MTBF: > 3.000.000 hrs
- Vibration: 20G / 7~2000 Hz
- Shock: 1500 G / 0.5 ms
- Dimension: 32.9 x 29.5 x 9.0 mm (LxWxH)

Requisiti di sistema

- A free SATA 7 pin port
- Power supply with a free Molex power connector

Contenuto della confezione

- 2 GB SATA Flash module
- Power cable