

Delock SATA 3 Gb/s Flash Modul 2 GB Vertical / Low Profile

Beskrivning

The SATA 3 Gb/s Flash Module is due to its very small size and high shock resistance ideal for application of mobile devices like IPCs, measuring systems as well as Digital Signage etc. Additional snap in will be provided by metal clips on the SATA connectors.



2 GB

Artikelnummer 54368

EAN: 4043619543687

Ursprungsland: Taiwan,
Republic of China

Paket: Antistatic cover

Specifikationer

- Capacity: 2 GB
- 7 pin SATA 3 Gb/s interface
- Chip: SLC (Single Level Cell)
- Operating voltage: 5 V +/-5%
- Operating temperature: 0 °C ~ + 70 °C
- Power consumption: read: 230 mA
write: 330 mA
idle: 130 mA
- Transfer modes: SATA 3 Gb/s, SATA 1.5 Gb/s, PIO 0~4, MDMA 0~2, UDMA 0~6
- S.M.A.R.T. & i-S.M.A.R.T. supported
- Maximum write cycles: 6000
- Read: up to 30 MB/s; write: up to 25 MB/s
- MTBF: > 3.000.000 hrs
- Vibration: 20G / 7~2000 Hz
- Shock: 1500 G / 0.5 ms
- Dimension: 32.9 x 29.5 x 9.0 mm (LxWxH)

Systemkrav

- A free SATA 7 pin port
- Power supply with a free Molex power connector

Paketets innehåll

- 2 GB SATA Flash module
- Power cable