Delock SATA 6 Gb/s Flash Module 16 GB vertical

Opis

The Delock SATA 6 Gb/s flash module is, due to its small size and high shock resistance, ideally suited for usage in mobile devices such as IPCs and measuring systems, as well as for the digital signage range. The module supports the SATA 6 Gb/s standard and is therefore convenient for applications that require fast read and write speeds. The metal clip at the SATA connector enables the module to snap in to your SATA port.



16 GB

Numer artykułu 54563

EAN: 4043619545636

Kraj pochodzenia: Taiwan, Republic Of China

Opakowanie: Antistatic cover

Specyfikacja

- Capacity: 16 GB
- Memory chip: Toshiba MLC, 2 channels
- Controller: ID107
- 7 pin SATA 6 Gb/s interface
- Transmission modes: SATA 6 Gb/s, SATA 3 Gb/s, SATA 1.5 Gb/s
- Operating voltage: 5 V +/- 5%
- Operating temperature: 0 °C ~ +70 °C
- Storage temperature: -55 °C ~ +95 °C
- Endurance:
  - Write / Erase: > 3,000 cycles
  - Read: unlimited
- Supports Write Protect, ATA Security and SMART (Self-Monitor Analysis and Reporting Technology)
- 255 MB/s read, 35 MB/s write
- Power consumption: 1.0 W (max.)
- Current demand:
  - Read: 180 mA
  - Write: 200 mA
  - Idle: 120 mA
- MTBF: > 3.000.000 hrs.
- Vibration: 20 G, 7 ~ 2000 Hz
- Shock: 1,500 G / 0.5 ms
- Dimensions (LxWxH): ca. 41.5 x 25.2 x 6.8 mm

© 2024 by Delock. Wszelkie pojawiające się tutaj nazwy i znaki należą do ich odpowiednich właścicieli. Błędy drukarskie, zmiany & pomyłki zastrzeżone.

Wymagania systemowe

- A free SATA 7 pin port
- Power supply with a free Molex power connector

Zawartość opakowania

- SATA Flash module
- Power cable

© 2024 by Delock. Wszelkie pojawiające się tutaj nazwy i znaki należą do ich odpowiednich właścicieli. Błędy drukarskie, zmiany & pomyłki zastrzeżone.