

# Delock Adapter USB 40 Gbps USB Type-C™ PD 3.0 100 W male to female angled 8K 60 Hz

## Description

This USB-C™ adapter by Delock can be used for the connection of USB-C™ devices. It can be also connected to a free USB-C™ port in order to prevent the interface from damage when it is under usage for high contact durability.



**Item no. 60056**

EAN: 4043619600564

Country of origin: China

Package: Zip poly bag

## Specification

- Connectors:
  - 1 x USB 40 Gbps USB Type-C™ male
  - 1 x USB 40 Gbps USB Type-C™ female
- Data transfer rate up to 40 Gbps
- USB Power Delivery (USB PD 3.0) support up to 100 watt
- Output current: up to 5 A
- Voltage: max. 20 V
- Supports DP Alt Mode
- Maximum resolution (depending on the system and the connected hardware):
  - DisplayPort 1.4 with DSC: up to 7680 x 4320 @ 60Hz
  - DisplayPort 1.4 with DSC: up to 3840 x 2160 @ 144 Hz
- Transmission of audio and video signals
- HDCP and HDR support
- Downwards compatible to USB 3.2, USB 2.0 and Thunderbolt™ 3
- Useable on both sides
- Housing material: PVC
- Colour: black
- Dimensions (LxWxH): ca. 2.0 x 1.3 x 0.8 cm

---

## System requirements

- A free USB-C™ interface

---

## Package content

- USB adapter

---

## Images



## General

Specification:	USB Type-C™ USB4
----------------	---------------------

## Interface

Connector 1:	1 x USB Type-C™ male
Connector 2:	1 x USB Type-C™ female

## Technical characteristics

Operating voltage:	20 V
Data transfer rate:	40 Gbps

## Physical characteristics

Housing material:	PVC
Length:	2.0 cm
Width:	1.3 cm
Height:	0.8 cm
Colour:	anthracite