

USB Adapter 40 Gbps USB Type-C™ PD 3.1 240 W male to female rotated angled left / right 8K 60 Hz metal

Description

This USB-C™ adapter by Delock can be used for the connection of USB-C™ devices. It can be also connected to a free USB-C™ port in order to prevent the interface from damage when it is under usage for high contact durability.



Item no. 60288

EAN: 4043619602889

Country of origin: China

Package: Zip poly bag

Technical details

- Connectors:
 - 1 x USB 40 Gbps USB Type-C™ male
 - 1 x USB 40 Gbps USB Type-C™ female
- Data transfer rate up to 40 Gbps
- USB Power Delivery (USB PD 3.1) support up to 240 watt
- Output current: up to 5 A
- Voltage: max. 48 V
- Supports DP Alt Mode
- Maximum resolution (depending on the system and the connected hardware):
 - DisplayPort 1.4 with DSC: up to 7680 x 43.1 @ 60Hz
 - DisplayPort 1.4 with DSC: up to 3840 x 2160 @ 144 Hz
- Transmission of audio and video signals
- HDCP and HDR support
- Downwards compatible to USB 3.2, USB 2.0 and Thunderbolt™ 3, Thunderbolt™ 4
- Useable on both sides
- Housing material: metal
- Colour: violet
- Dimensions (LxWxH): ca. 25.4 x 12 x 8 mm

System requirements

- A free USB-C™ interface
-

Package content

- USB adapter
-

Images



General

| | |
|----------------|-------------|
| Specification: | USB 40 Gbps |
|----------------|-------------|

Interface

| | |
|--------------|------------------------|
| Connector 1: | 1 x USB Type-C™ male |
| Connector 2: | 1 x USB Type-C™ female |

Technical characteristics

| | |
|----------------------------|---|
| Operating voltage: | 48 V |
| Data transfer rate: | 40 Gbps |
| Maximum screen resolution: | 7680 x 4320 @ 60 Hz 3840 x 2160 @ 144 Hz |

Physical characteristics

| | |
|-------------------|--------|
| Housing material: | metal |
| Length: | 2.5 cm |
| Width: | 1.2 cm |
| Height: | 0.9 cm |
| Colour: | violet |

Manufacturer information

Street Beeskowdamm 13/15
 Postal code 14167
 City Berlin
 Country Deutschland
 E-Mail info@delock.de
 Website www.delock.de

