

Delock USB Adapter 40 Gbps USB Type-C™ PD 3.1 240 W male to female rotated angled left / right 8K 60 Hz metal

Description

This USB-CTM adapter by Delock can be used for the connection of USB-CTM devices. It can be also connected to a free USB-CTM port in order to prevent the interface from damage when it is under usage for high contact durability.



Item no. 60288

EAN: 4043619602889 Country of origin: China Package: Zip poly bag

Specification

- · Connectors:
 - 1 x USB 40 Gbps USB Type-C™ male
 - 1 x USB 40 Gbps USB Type-CTM female
- Data transfer rate up to 40 Gbps
- USB Power Delivery (USB PD 3.1) support up to 240 watt
- Output current: up to 5 A
- Voltage: max. 48 V
- Supports DP Alt Mode
- Maximum resolution (depending on the system and the connected hardware):

DisplayPort 1.4 with DSC: up to 7680 x 43.1 @ 60Hz

DisplayPort 1.4 with DSC: up to 3840 x 2160 @ 144 Hz

- Transmission of audio and video signals
- HDCP and HDR support
- Downwards compatible to USB 3.2, USB 2.0 and Thunderbolt™ 3, Thunderbolt™ 4
- Useable on both sides
- · Housing material: metal
- · Colour: anthracite



• Dimensions (LxWxH): ca. 2.5 x 1.2 x 0.9 cm

System requirements

• A free USB-CTM interface

Package content

• USB adapter

Images







General

Specification: USB Type-C™ USB4

Interface

Connector 1:	1 x USB Type-C™ male
Connector 2:	1 x USB Type-C™ female

Technical characteristics

Operating voltage:	48 V
Data transfer rate:	40 Gbps
Maximum screen resolution:	7680 x 4320 @ 60 Hz 3840 x 2160 @ 144 Hz

Physical characteristics

Housing material:	metal
Length:	2.5 cm
Width:	1.2 cm
Height:	0.9 cm
Colour:	anthracite