

Delock Adapter USB 2.0 Type-A to 1 x Serial RS-232 D-Sub 9 pin male with ferrite core 0.25 m

Description

This adapter by Delock enables the connection of a serial device via a USB Type-A port. The additional ferrite core on the cable prevents interference signals and improves data transmission.



0,25 m

Item no. 61549

EAN: 4043619615490

Country of origin: China

Package: Retail Box

Specification

- Connectors:
 - 1 x USB 2.0 Type-A male
 - 1 x serial RS-232 DB9 male with screws
- Chipset: FTDI FT232RL
- 1 x ferrite core
- Screw type: #4-40 UNC
- Compatible with USB 3.0, USB 2.0, and USB 1.1
- Signals: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Data transfer rate up to 921.6 Kbps
- Colour: black
- Cable length incl. connectors: ca. 0.25 m

System requirements

- Linux Kernel 5.15 or above
- Mac OS 12.4 or above
- Windows 8.1/8.1-64/10/10-64/11

- PC or laptop with a free USB Type-A port
-

Package content

- USB Type-A to 1 x serial adapter
 - Driver CD
 - User manual
-

Images



General

Function:	Plug & Play
Specification:	RS-232 (EIA / TIA) USB 1.1 USB 2.0
Supported operating system:	Linux Kernel 2.6 or above Mac OS 10.9 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows Server 2008 R2 Windows Server 2012 R2 Windows Server 2012 Windows Server 2016 Windows Server 2019 Windows 11

Interface

Connector 2:	1 x serial Sub-D 9 male with screws
--------------	-------------------------------------

Technical characteristics

Chipset:	FTDI FT232RL
Data transfer rate:	up to 921.6 Kbps
FIFO:	128 byte 256 Byte
Data transmission:	asynchronous full duplex Bi-directional Half duplex
UART:	USB to serial UART

Physical characteristics

Cable colour:	black
---------------	-------

Cable length incl. connector:	0.25 m
Pin finishing:	gold-plated
Screw type:	#4-40 UNC
Shielding:	double
Colour:	black