

Delock Converter eSATA and USB 2.0 > 2 x SATA with RAID

Description

The Delock converter by IOI enables the connection of SATA HDD. The switch on the front allows the setting of several RAID functions.



Item no. 61576

EAN: 4043619615766

Country of origin: Taiwan,
Republic of China

Package: Antistatic cover

Specification

- IOI item number: ESU2DSATA10
- Connectors:
 - 1 x external USB 2.0-B
 - 1 x external eSATA
 - 2 x internal SATA
- Data transfer rates:
 - USB 2.0-B up to 480 Mb/s
 - eSATA up to 3 Gb/s
 - SATA up to 3 Gb/s
- Supports NCQ
- Supports OHCI, UHCI and EHCI
- Supports RAID 0, 1, Big, JBOD, SAFE33, SAFE50 and GUI
- GUI (grafical user interface) e.g. configure with SteelVine Manager
- Drive Locking with password lock
- Dimensions (LxWxH): 5.28 x 8.33 x 2.16 cm
- LED indicators for link and activity
- Power input: 1.5 Watt
- Failure alarm

System requirements

- Windows 2000/XP/Server-2003/Vista, Mac OS X 10.5 or higher
- PC or Notebook with one free eSATA or USB port
- SATA host controller with SATA port multiplier support

Package content

- Converter