


# Delock M.2 Adapter M.2 > 2 x RJ45 Gigabit LAN port (USB 3.0)

## Description

This M.2 module by Delock expands a system by two RJ45 Gigabit LAN ports.

**M.2**



## Specification

- Connector: 1 x 67 pin M.2 NGFF key B male> 2 x Gigabit LAN RJ45 female
- Interface: USB 3.0
- Form factor: M.2 2260
- Chipset: RTL8153AI
- Maximum power consumption: 1.45 W (3.3 V, 440 mA)
- Vibration: 5G @ 7 ~ 2000 Hz
- Shock: 50G @ 0.5 ms
- Operation temperature: 0°C ~ +70°C
- Storage temperature: -55°C ~ +95°C
- Dimensions (LxWxH): ca. 60.0 x 22.0 x 6.1 mm
- Needs CDC-ECM for Linux support

## Item no. 62684

EAN: 4043619626847

Country of origin: China

Package: • Antistatic cover


## System requirements

- Windows 7/7-64/8/8-64/8.1/8.1-64/10/10-64, Linux Kernel 3.x
- A free M.2 NGFF Key B slot with at least 60 mm length
- M.2 slot with USB interface

## Package content

- M.2 NGFF module
- Daughter Board
- Connection cable 32 cm
- Slot bracket

## Images



**General**

Supported operating system:	Needs Linux CDC-ECM support Linux Kernel 3.x Windows XP 32-bit Windows XP 64-bit Windows 7 32-bit Windows 7 64-bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit
-----------------------------	---

Storage temperature range:	-55 °C ~ 95 °C
----------------------------	----------------

**Interface**

connector:	M.2 NGFF on USB basis
Connector 1:	2 x RJ45 Gigabit LAN

**Technical characteristics**

Operating temperature:	0 °C ~ 70 °C
Shock:	50 G @ 0.5 ms
Current consumption:	440 mA
Vibration:	5 G @ 7 ~ 2000 Hz

**Physical characteristics**

Length:	60 mm
Width:	22 mm
Height:	6.1 mm