

HDMI Audio Extractor 4K 30 Hz

Description

This adapter by Delock can be used to extract the audio signal from an HDMI transmission. While the video signal is displayed on a TV or monitor, the audio signal can be sent digital (S/PDIF) or analogue (stereo) to other devices, such as headphones or a surround receiver.



Item no. 62692

EAN: 4043619626922

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - Input:
 - 1 x HDMI-A 19 pin female
 - 1 x 5 V DC jack 2.1 x 5.5 mm
 - Output:
 - 1 x HDMI-A 19 pin female
 - 1 x 3.5 mm 3 pin stereo jack female (audio)
 - 1 x TOSLINK female S/PDIF
 - 1 x RCA female S/PDIF
- Switchable between stereo and 5.1 channel
- High Speed HDMI, 3D and HDCP 1.4
- Output with HDMI repeater function
- Resolution up to 3840 x 2160 @ 30 Hz (8 bit), 1920 x 1080 @ 60 Hz (12 bit)
- Video bandwidth up to 300 MHz / 3 Gb/s per channel, 9 Gb/s max.
- Supports all common 2.0 and 5.1 audio formats: LPCM, Dolby Digital, DTS Audio
- Supported sample rates: 16 / 20 / 24 bit, 32 / 44.1 / 48 / 88.2 / 96 kHz (depending on the system and the connected devices)
- CEC and HDMI audio routed to the output (pass-through)
- Chipset: CS4344, 24 bit / 192 kHz
- Robust metal housing
- Power consumption: max. 2.5 W
- Dimensions (LxWxH): ca. 71 x 61 x 21 mm

Power supply specification

- Power supply type: Euro wall power plug
- Model identifier: FJ-SW1160501000DE
- Input voltage: 100 - 240 V
- Input AC frequency: 50 / 60 Hz
- Input current: 0.3 A
- Output voltage / Output current / Output power: 5.0 V / 1.0 A / 5.0 W
- Average active efficiency: 75.7 %
- No-load power consumption: 0.07 W
- DC power connector: 5.5 x 2.1 mm
- Power supply cable length: ca. 1.5 m
- Ground outside, plus inside

System requirements

- A free HDMI-A female

Package content

- HDMI Audio Extractor
- Mounting brackets and screws
- USB power cable, length: ca. 0.5 m
- Power supply
- User manual

Images



General

Specification:	DTS Audio Dolby Digital HDCP 1.4 HDMI 1.4 LPCM
----------------	------------------------------------------------------------

Interface

Output:	1 x 3.5 mm 3 pin stereo jack female 1 x RCA female 1 x TOSLINK female 1 x HDMI-A female
Input:	1 x 5 V DC female 5,5 mm x 2,1 mm 1 x HDMI-A female

Technical characteristics

Chipset:	Cirrus CS4344
Maximum screen resolution:	3840 x 2160 @ 30 Hz
Video bandwidth:	300 MHz

Physical characteristics

Housing colour:	black
Housing material:	metal
Length:	71 mm
Width:	61 mm
Height:	21 mm

Power supply

Power supply type:	Euro wall power supply
Input voltage:	AC 100 - 240 V / 50 - 60 Hz / 0.3 A
Power supply output:	5.0 V / 1.0 A

Power supply connector:	DC male 5.5 mm x 2.1 mm
Cable length of power supply:	1 m

Manufacturer information

Street Beeskowdamm 13/15
Postal code 14167
City Berlin
Country Deutschland
E-Mail info@delock.de
Website www.delock.de

