


# Delock Converter SATA / USB 3.1 Type-B female > M.2 / mSATA Slot

## Description

This Delock converter enables the connection of a M.2 SSD in 2280, 2260, 2242 and 2230 format or an mSATA SSD in half size or full size format. If both slots are occupied, only the M.2 SSD can be used. The converter can be installed into the system through a SATA or USB interface.

## Specification

- Connector:
  - 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) Type-B female
  - 1 x USB 3.0 Type-B female (optional for power supply) >
  - 1 x 67 pin M.2 key B slot
  - 1 x mSATA slot (half size / full size)
- Interface: SATA
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key B or key B+M based on SATA
- Maximum height of the components on the module: 1.35 mm application of double-sided assembled modules supported
- LED indicator
- Maximum current for M.2 or mSATA module: 3 A
- Dimensions (LxWxH): ca. 100 x 85 x 15 mm

## System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 4.6
- A free SATA interface or
- A free USB interface

## Package content

- Converter
- Screws for M.2 module and mSATA module
- User manual




## Item no. 62732

EAN: 4043619627325

Country of origin: Taiwan, Republic of China

Package: Retail Box

## Images



General	
Slot:	SATA
Supported module:	M.2 modules in format 2280, 2260, 2242 and 2230 with key B or key B+M based on SATA
Maximum height of the components on the module:	1.5 mm application of double-sided assembled modules supported
Interface	
Connector 1:	1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) Type-B female
Connector 2:	1 x USB 3.0 Type-B female (optional power supply)
connector 3:	1 x 67 pin M.2 key B slot
connector 4:	1 x mSATA slot (half size / full size)
Physical characteristics	
Length:	100 mm
Width:	85 mm
Height:	15 mm