
Delock 3.5” / 5.25” USB 3.0 Hub 4 Port

Description

This hub by Delock can be installed into a 3.5″ or 5.25″ bay of the PC. It will be connected internally via a USB 3.0 pin header male on the motherboard. Up to four USB devices, e.g. docking stations, card readers, external enclosures etc. can be connected. One USB 3.0 Type-A female supports the Battery Charging and Fast Charge function, e.g. to charge a smartphone faster. The slide switch can be used to select whether this port is to be used as a fast charging port or as a data port with a simple charging function.



Item no. 62903

EAN: 4043619629039

Country of origin: China

Package: Retail Box

Specification

- Connectors:
  external:
  3 x USB 3.0 Type-A female
  1 x USB 3.0 Type-A female - Battery Charging specification BC1.2
  internal:
  1 x USB 3.0 Type-B female
  1 x 4 pin power connector
  1 x SATA 15 pin power connector
- 1 slide switch for the Battery Charging Port
- Chipset: VLI VL811
- Data transfer rate up to:
  SuperSpeed USB 5 Gbps,
  Hi-Speed 480 Mbps,
  Full-Speed 12 Mbps,
  Low-Speed 1.5 Mbps
- Cable data: 1 x USB 3.0 Type-B female to 1 x 19 pin USB 3.0 pin header female, length ca. 62 cm
- Hot Swap, Plug & Play

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.


System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 2.6.x / Kernel 4.x.x, Mac OS 10.9
- PC with a free 3.5″ or 5.25″ bay
- Mainboard with a free 19 pin USB 3.0 pin header male
- Power supply with a free 4 pin Molex or 15 pin SATA power connector

Package content

- 3.5″ Hub USB 3.0
- 5.25″ frame
- USB 3.0 cable
- Screws
- User manual

Images



© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

General

Form factor:	3.5" 5.25"
Function:	Battery Charging BC1.2 Hot Plug Hot Swap
Supported operating system:	Linux Kernel 2.6 or above Mac OS 10.9 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

Interface

External:	4 x USB 5 Gbps Type-A female
Internal:	1 x USB 5 Gbps Type-B female 1 x 4 pin power connector 1 x SATA 15 pin power connector

Technical characteristics

Chipset:	VLI VL811
Data transfer rate:	USB 5 Gbps up to 5 Gb/s

Physical characteristics

Colour:	black

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.