

Delock Adaptor USB Type-C™ > 1 x interfață serială DB9 RS-232

Descriere scurta

Acest adaptor USB Type-C™ la serial de la Delock oferă o interfață compatibilă RS-232 DB9 pentru imprimante, instrumente de măsură, controale, dispozitive IoT etc.



ca. 1,8 m

Specificatii

- Conectori:
1 x USB Type-C™ tată >
1 x RS-232 seriale DB9, tată
- Chipset: Prolific PL2303 HXD
- Tipul șurubului: #4-40 UNC
- Compatibil cu USB 2.0, și USB 1.1 viteză completă de 12 Mbps
- Rată de transfer a datelor de până la 1 Mbps
- Semnale: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Paritate: egală, impară, niciuna, marcă, spațiu
- Bit de oprire: 1, 1,5, 2
- Bit de date: 5, 6, 7, 8
- Controlul debitului: niciunul, Xon/Xoff, RTS/CTS
- FIFO: 512 biți buffer bi-direcțional
- Lungime cablu: cca 1,8 m

Cerinte de sistem

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 2.6.31 / Kernel 4.x.x, Mac ex OS 10.12, Android ex 4.4
- PC sau laptop cu un port USB Type-C™ sau Thunderbolt™ 3 liber

Pachetul contine

- Cablu Adaptor USB Type-C™ > 1 x RS-232 DB9 Serial
- CD cu drivere
- Manual de utilizare

Nr. 62964


EAN: 4043619629640

Țara de origine: HONG KONG

Pachet: Retail Box



Imagini



General	
Function:	Plug & Play
Specification:	RS-232 (EIA / TIA) USB 1.1 USB 2.0
Supported operating system:	Mac OS 10.12 sau superior Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Android 4.4 sau superior Linux Kernel 3.3 sau superior
Interface	
Conector 1:	1 x USB Type-C™ tată
Conector 2:	1 x Serial RS-232 DB9 male
Technical characteristics	
Chipset:	Prolific PL2303HxD
Data transfer rate:	up to 921.6 Kbps
FIFO:	512 byte
Signal transmission:	TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
Data transmission:	asynchronous full duplex
Voltage:	USB Bus powered (no additional power supply required)
Physical characteristics	
Cable length incl. connector:	1.8 m
Tipul șurubului:	#4-40 UNC
Colour:	negru