


# Delock External Industry Hub 10 x USB 3.0 Type-A with 20 kV ESD protection

## Description

This solid industry capable USB hub by Delock can be connected to a computer via the USB Type-A interface. It expands the computer by ten USB Type-A connectors. If necessary, an optional power supply or an optional power cable can be connected to the power socket.



**Item no. 63919**

EAN: 4043619639199

Country of origin: China

Package: Retail Box

## Specification

- Connectors:
  - 1 x USB 3.0 Type-B female >
  - 10 x USB 3.0 Type-A female
  - 1 x 9 – 40 V DC jack
  - 1 x 3 pin terminal power connector
- Chipset: VIA VL817
- Data transfer rate up to:
  - SuperSpeed USB 5 Gbps,
  - Hi-Speed 480 Mbps,
  - Full-Speed 12 Mbps,
  - Low-Speed 1.5 Mbps
- 11 x LED indicator
- USB ports with screw holes
- Robust metal housing
- Pitch of screw hole USB Type-A: ca. 19 mm
- Pitch of screw hole USB Type-B: ca. 19.5 mm
- Thread size: M3
- Removable wall-mount brackets

- Power supply: Bus-powered or Self-powered
- Flexible power supply with 9 V to 40 V
- Automatic detection of the input polarity of the power connectors
- ESD protection up to 20 kV for all ports
- Dimensions (LxWxH): ca. 202 x 80 x 32 mm
- Colour: black
- Plug & Play

---

## Specification of power connector

- 9 - 40 V
- Dimensions:
  - inside:  $\varnothing$  ca. 2.1 mm
  - outside:  $\varnothing$  ca. 5.5 mm
  - length: ca. 9 mm

---

## System requirements


- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 3.16.x, Mac ex OS 10.9
- PC or laptop with a free USB Type-A port

---

## Package content

- Hub USB
- 1 x cable USB A male to USB B male, length ca. 1 m
- 2 x wall mounting brackets
- 1 x mounting for 35 mm DIN rail
- 1 x 3 pin terminal block
- User manual

## Images



## General

Function:	Battery Charging BC1.2 Plug & Play
Mounting type:	DIN rail Screw mounting
Supported operating system:	Linux Kernel 3.16 or above Mac OS 10.9 or above Windows 10 32-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
LED indicator:	11 x

## Interface

Connector 1:	1 x USB 5 Gbps Type-B female
Connector 2:	10 x USB 5 Gbps Type-A female - Battery Charging specification BC1.2
connector 3:	1 x 9 – 40 V DC jack
connector 4:	1 x 3 pin terminal power connector

## Physical characteristics

Length:	202 mm
Width:	80 mm
Height:	32 mm
Colour:	black