

Delock External USB 2.0 Sound Adapter Virtual 7.1 - 24 bit / 96 kHz with S/PDIF

Description

The USB sound adapter by Delock expands the computer with an additional sound card. Headphones or speakers can be connected. The audio output has a combo connector and can be used as a conventional analog stereo output or as an optical digital (S/PDIF) output. The adapter can playback audio files with up to 24 bit / 96 kHz.



Item no. 63926

EAN: 4043619639267

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - 1 x USB 2.0 Type-A male >
 - 1 x 3.5 mm 3 pin stereo jack female microphone
 - 1 x 3.5 mm 3 pin stereo jack female (analogue) / S/PDIF (digital) speaker
- Chipset: C-Media CM6533
- Functional keys: Volume-UP, Volume-Down, Mute
- USB audio device specification 1.0
- Up to 24 Bit / 96 kHz sampling rate for playback and 16 Bit / 48 kHz for recording
- Supports virtual 7.1 channel Sound
- USB bus powered
- Plug & Play

System requirements


- Chrome OS 61.0 or above
- Mac OS 10.9 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64/11

- PC or laptop with a free USB Type-A port

Package content

- USB sound adapter

Images



General

Function:	Plug & Play
Specification:	USB 2.0
Supported operating system:	Chrome OS 61.0 or above Mac OS 10.9 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

Interface

Connector 1:	1 x USB 2.0 Type-A male
Connector 2:	1 x 3.5 mm 3 pin stereo jack female microphone
connector 3:	1 x speaker 3.5 mm stereo jack female (analogue) output / S/PDIF (digital) output

Technical characteristics

Chipset:	C-Media CM6533
----------	----------------

Herstellerinformation

Strasse	Beeskowdamm 13/15
PLZ	14167
Ort	Berlin
Land	Deutschland
E-Mail	info@delock.de
Webseite	www.delock.de