Delock 3.5″ USB 3.2 Gen 1 Front Panel 1 x USB Type-C™ + 2 x USB Type-A + SD and Micro SD slot

Description

This front panel by Delock can be installed into a free 3.5″ bay of a computer. It has two USB 3.2 Gen 1 Type-A and one USB 3.2 Gen 1 Type-C port. It will be connected to the motherboard internally via a pin header male port.

Integrated Card Reader
In addition, the hub with integrated card reader expands the PC by an SD and a Micro SD slot.



Item no. 64050

EAN: 4043619640508

Country of origin: China

Package: Retail Box

Specification

- Connectors:
  external:
  1 x SuperSpeed USB (USB 3.2 Gen 1) USB Type-C™ female
  2 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female
  1 x SD slot
  1 x Micro SD slot
  internal:
  1 x 19 pin USB 3.0 pin header female port on the cable
  1 x SATA 15 pin power connector
- Chipset: Genesys Logic GL3520, GL3224
- Data transfer rate up to:
  SuperSpeed 5 Gbps,
  Hi-Speed 480 Mbps,
  Full-Speed 12 Mbps,
  Low-Speed 1.5 Mbps
- The Card Reader supports following memory cards:
  1. Slot Secure Digital
  SD, SD3.0 UHS-I, SD High Capacity (SDHC), SD Ultra, SDHC Ultra, SDXC, MMC-I, MMC-II, MMC 4.0, Mini SD, Mini SDHC, MMCmobile, RS-MMC, RS-MMC 4.0

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

2. Slot Micro Secure Digital
MicroSD, Micro SDHC, Micro SDHC Ultra, T-Flash, MMCmicro

- Cable data:
  1 x 19 pin USB 3.0 pin header female cable, length ca. 54 cm (without connectors)
- 3.5″ metal frame
- Colour: black
- Hot Swap, Plug & Play

System requirements

- Linux Kernel 3.3 or above
- Windows 8.1/8.1-64/10/10-64
- PC with one free 3.5″ bay
- Motherboard with a free 19 pin USB 3.0 pin header male
- Power supply with SATA 15 pin receptacle

Package content

- 3.5″ front panel
- USB 3.0 pin header female cable
- Screws
- User manual

Images



© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

General

Form factor:	3.5"
Function:	Hot Swap Plug & Play
Supported operating system:	Linux Kernel 3.3 or above Windows 10 64-Bit Windows 8.1 64-Bit

Interface

External:	1 x Micro SD Slot 1 x SD slot 1 x USB 5 Gbps USB Type-C™ female 2 x USB 5 Gbps Type-A female
Internal:	1 x 19 pin USB 5 Gbps pin header female 1 x SATA 15 pin power connector

Technical characteristics

Chipset:	Genesys Logic GL3520 Genesys Logic GL3224
Data transfer rate:	USB 5 Gbps up to 5 Gb/s

Physical characteristics

Housing material:	metal
Length:	102 mm
Width:	95 mm
Height:	26 mm
Colour:	black

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.