

# Delock Externer USB 3.1 2 Port Typ-A und 2 Port USB Type-C™ Hub mit 10 Gbps

## Description

This USB Hub by Delock can be connected to a computer via the USB Type-C™ interface. It expands the computer by **two USB Type-A** ports and **two USB-C™** ports.

### USB Power Delivery support up to 60 watt

The included power supply provides power to the connected devices on the front.

With a USB-C™ power supply, laptops such as the MacBook or Chromebook can be charged during operation. The hub can also be used without a power supply.



## Specification

- Connectors:
  - 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female
  - 2 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) Type-A female
  - 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female
  - 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ Power Delivery female
  - 1 x DC 5 V power connector
- Chipset: Realtek RTS5429
- Data transfer rate up to:
  - SuperSpeed USB 10 Gbps,
  - SuperSpeed USB 5 Gbps,
  - Hi-Speed 480 Mbps,
  - Full-Speed 12 Mbps,
  - Low-Speed 1.5 Mbps
- Output power for host: max. 60 W
- 1 x LED indicator
- Colour: black
- Dimensions (LxWxH): ca. 92 x 54 x 19 mm
- Plug & Play

## Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.4 A
- Output: 5 V / 2 A
- Ground outside, plus inside
- Dimensions:
  - inside: ø ca. 2.5 mm
  - outside: ø ca. 5.5 mm
  - length: ca. 10 mm

## System requirements

- Chrome OS
- Linux Kernel 4.6 or above
- Mac OS 10.13.3 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-C™ port

## Package content

- Hub USB

## Item no. 64054

EAN: 4043619640546

Country of origin: China

Package: Retail Box



- 1 x Cable USB-C™ male to USB-C™ male, length ca. 60 cm
- Power supply
- User manual

### Images



General	
Function:	Plug & Play
Specification:	SuperSpeed USB 10 Gbps (USB 3.1 Gen 2)
Supported operating system:	Chrome OS Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Linux Kernel 4.6 or above Mac OS 10.13.3 or above
LED indicator:	1 x
Interface	
Connector 1:	1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female
Connector 2:	2 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) Type-A female
connector 3:	2 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female
connector 4:	1 x 5 V DC jack
Technical characteristics	
Chipset:	Realtek RTS5429
Data transfer rate:	10 Gbps
Physical characteristics	
Length:	92 mm
Width:	54 mm
Height:	19 mm
Colour:	black
Power supply	
Input:	AC 100 - 240 V / 50 - 60 Hz / 0.4 A
Output:	5 V / 2 A
Connector:	DC plug 5.5 mm x 2.5 mm