

Delock 3.5" USB 3.2 Gen 1 Front Panel 2 x USB Type-C™ + 2 x USB Type-A

Description

This hub by Delock can be installed into a 3.5" bay of the PC. It will be connected internally via a USB pin header male on the motherboard. It has two USB Type-A and two USB Type-C™ ports.



Specification

- Connectors:
 - external:
 - 2 x SuperSpeed USB 5 Gbps (USB 3.2 Gen 1) USB Type-C™ female
 - 2 x SuperSpeed USB 5 Gbps (USB 3.2 Gen 1) Type-A female
 - internal:
 - 1 x 19 pin USB 3.0 pin header female port on the cable
 - 1 x 4 pin power connector
- Chipset: VIA VL817
- Data transfer rate up to:
 - SuperSpeed 5 Gbps,
 - Hi-Speed 480 Mbps,
 - Full-Speed 12 Mbps,
 - Low-Speed 1.5 Mbps
- Cable data:
 - 1 x 19 pin USB pin header female cable, length ca. 54 cm (without connectors)
 - 1 x power cable 4 pin female to 1 x SATA 15 pin plug, length ca. 17 cm (without connectors)
- 3.5" metal frame
- Colour: black
- Hot Swap, Plug & Play

System requirements

- Linux Kernel 3.3 or above
- Windows 8.1/8.1-64/10/10-64/11
- PC with one free 3.5" bay
- Motherboard with a free 19 pin USB pin header male
- Power supply with SATA 15 pin receptacle

Package content

- 3.5" Hub
- USB cable
- Power cable
- Screws
- User manual

Item no. 64155

EAN: 4043619641550

Country of origin: China

Package: Retail Box

Images



General	
Form factor:	3.5"
Function:	Hot Swap Plug & Play
Supported operating system:	Linux Kernel 3.3 or above Windows 10 64-bit Windows 8.1 64-bit Windows 11
Interface	
External:	2 x USB Type-C™ Buchse 2 x USB 3.0 Type-A female
Internal:	1 x 4 pin power connector 1 x 19 pin USB 3.0 pin header female
Technical characteristics	
Chipset:	VIA VL817
Data transfer rate:	USB 3.0 up to 5 Gb/s
Physical characteristics	
Housing material:	metal
Length:	102 mm
Width:	95 mm
Height:	26 mm
Colour:	black