

Delock M.2 Key A+E to PCIe x1 NVMe Adapter angled with 20 cm cable

Description

This adapter by Delock can be used to **connect a PCI Express card to an M.2 slot**. The flexible cable allows a space-saving installation inside the computer case. The additional power connector can supply the PCIe card with 12 V voltage if required.



Item no. 64217

EAN: 4043619642175 Country of origin: China

Package: Box

Specification

- Connectors:
 - 1 x M.2 key A+E male
 - 1 x PCI Express x1, V4.0
 - 1 x 4 pin power connector
- Interface: PCIe / NVMe (1 Lane)
- Form factor: M.2 2230
- Cable gauge: 30 AWG
- Bootable, ex UEFI version 2.3.1
- Supports NVM Express (NVMe)
- Length without connectors: ca. 20 cm

System requirements

• A free M.2 port with key A or key E

Package content



- Adapter
- Screwdriver
- Mounting material
- Power cable 4 pin to SATA, length ca. 15 cm
- User manual

Images







General

Form factor:	M.2 2230
Function:	Bootable, ex UEFI 2.3.1 NVM Express (NVMe)

Interface

Connector 1:	1 x M.2 key A+E male
Connector 2:	1 x PCI Express x1, V4.0
connector 3:	1 x 4 pin power connector

Physical characteristics

Cable length: 20 cm (without connector)