

Delock Active mini DisplayPort 1.4 to HDMI Adapter 4K 60 Hz (HDR)

Description

This adapter by Delock enables the connection of an HDMI monitor to the system via a free mini DisplayPort interface. The adapter supports a resolution up to 4K Ultra HD at 60 Hz and is backward compatible to Full-HD 1080p.

Active adapter

The adapter offers an active conversion, thus it is also suitable for graphics cards that are not capable of outputting DP++ signals.



Item no. 65302

EAN: 4043619653027

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - 1 x mini DisplayPort male >
 - 1 x HDMI-A female
- Chipset: Parade PS186
- DisplayPort 1.4 and High Speed HDMI specification
- Active converter, for graphics cards with DP and DP++ output
- Signal direction: mini DisplayPort input > HDMI output
- Cable gauge:
 - 32 AWG data line
 - 28 AWG power line
- Cable diameter: ca. 5 mm
- Connectors: gold-plated
- Transmission of audio and video signals
- Data transfer rate up to 18 Gbps
- Resolution up to 3840 x 2160 @ 60 Hz
(depending on the system and the connected hardware)
- Supports HDR
- Supports HDCP 1.4 and 2.3
- 1 x ferrite core

- Cable length without connectors: ca. 20 cm
- Colour: black

System requirements

- A free mini DisplayPort female

Package content

- Adapter mini DisplayPort to HDMI

Images



General

Specification:	DisplayPort 1.4 HDCP 1.4 HDCP 2.3 HDMI 2.0 HDR
----------------	--

Interface

Connector 1:	1 x mini DisplayPort male
Connector 2:	1 x HDMI-A female

Technical characteristics

Chipset:	Parade PS186
Data transfer rate:	18 Gbps
Maximum screen resolution:	3840 x 2160 @ 60 Hz

Physical characteristics

Ferrite core:	1 x
Cable length:	20 cm
Pin finishing:	gold-plated
Cable gauge:	32 AWG data line 28 AWG power line
Colour:	grey black
Cable diameter:	5 mm

Herstellerinformation

Strasse	Beeskowdamm 13/15
PLZ	14167
Ort	Berlin
Land	Deutschland
E-Mail	info@delock.de
Webseite	www.delock.de