

# Delock HDMI Ethernet Extender Set by TCP/IP

## Description

This HDMI Extender Set by Delock allows HDMI signals to be transmitted over a TCP/IP network. The transmitter and receiver can be connected with a network cable of up to 100 m. Alternatively both devices can be connected via a switch, the distance between the HDMI source and the display device can then be 200 m.



## Specification

- Connectors:
  - 1 x RJ45 jack
  - 1 x HDMI-A 19 pin female
  - 1 x DC 5.5 x 2.1 mm female
- Following TCP/IP standard (Broadcasting)
- M-JPEG encoding / decoding up to 1080p @ 60 Hz
- Supported resolutions: 480i / 480p / 576i / 576p / 720p / 1080i / 1080p
- Supports EDID und HDCP
- Video bandwidth up to 165 MHz / 1.65 Gb/s
- Optional: simultaneous operation of multiple receivers
- Power consumption: max. 2.5 W
- Dimensions (LxWxH): ca. 103 x 84 x 25 mm

## Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:
  - inside: ø ca. 2.1 mm
  - outside: ø ca. 5.5 mm
  - length: ca. 9 mm

## System requirements

- HDMI cable
- One Cat.5e or Cat.6 network cable
- Switch with VLAN or IGMP Snooping

## Package content

- HDMI Extender TCP/IP (sender)
- HDMI Extender TCP/IP (receiver)
- 2 x power supply
- User manual

## Item no. 65494

EAN: 4043619654949

Country of origin: China

Package: • White Box



Images

