

Delock USB Microphone with base and Touch-Mute Button

Description

This USB microphone by Delock can be used for voice and vocal transmissions. The rubberized base provides a non-slip stand and the gooseneck allows the microphone to bend in the ideal direction. The LED ring indicates that the microphone is ready for operation by means of a blue or red light and the touch mute button can be used to mute the microphone.



Item no. 65868

EAN: 4043619658688 Country of origin: China Package: Retail Box

Specification

• Connector: 1 x USB 2.0 Type-A reversible male

• Sensitivity: -37 dB +/- 3 dB

• Frequency range: 70 Hz - 15 kHz

• Impedance: 2.2 kOhm +/- 30% at 1 kHz

• Sample rate: 16 Bit / 48 kHz

• Touch Mute-Button

Gooseneck

• Status LED

• Rubber Base

· Colour: black

• Cable length: ca. 1.7 m

• Dimensions (LxWxH): ca. 140 x 60 x 60 mm

· USB bus powered

• Plug & Play

System requirements



- Linux Kernel 3.3 or above
- Mac OS 10.9 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- USB microphone
- User manual

Images













General

| Function: | Plug & Play |
|-----------------------------|--|
| Supported operating system: | Linux Kernel 3.3 or above Mac OS 10.9 or above Windows 10 32-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit |

Interface

| connector: 1 x USB 2.0 Type-A reversible male |
|---|
|---|

Technical characteristics

| Frequency range: | 70 Hz - 15 kHz |
|------------------|---|
| Impedance: | 2.2 kOhm +/- 30% at 1 kHz |
| Voltage: | USB Bus powered (no additional power supply required) |
| Sensibility: | -37 dB +/- 3 dB |
| Sample rate: | 16 Bit / 48 kHz |

Physical characteristics

| Cable length: | 1.7 m |
|---------------|--------|
| Length: | 140 mm |
| Width: | 60 mm |
| Height: | 60 mm |
| Colour: | black |