

# Delock Adapter SuperSpeed USB (USB 3.2 Gen 1) with USB Type-C<sup>™</sup> male > Gigabit LAN 10/100/1000 Mbps compact black

## Description

The adapter by Delock expands a PC or laptop by one network interface via the USB Type-C<sup>TM</sup> interface. In addition, the adapter can also be operated on a Thunderbolt<sup>TM</sup> 3 interface.



#### Item no. 65904

EAN: 4043619659043 Country of origin: China Package: Retail Box

## **Specification**

Connectors:

1 x USB 5 Gbps USB Type-C<sup>™</sup> male

- 1 x Gigabit LAN RJ45 jack
- Chipset: Realtek RTL8153
- SuperSpeed USB 5 Gbps specification
- Data transfer rate: Ethernet up to 10 Mbps (Half/Full Duplex) Fast Ethernet up to 100 Mbps (Half/Full Duplex) Gigabit Ethernet up to 1000 Mbps (Half/Full Duplex)
- Compatible with: IEEE 802.3: 10BASE-T IEEE 802.3u: 100BASE-TX IEEE 802.3ab: 1000BASE-T
- Supports Auto MDI-X (automatic detection of standard or crossover network cable)
- Supports IEEE 802.3az (Energy Efficient Ethernet)
- Supports IEEE 802.1Q Virtual LAN (VLAN)
- Support full duplex operation with IEEE 802.3x flow control and half duplex operation with back-pressure flow

### **DATASHEET**



control

- Supports 9k Jumbo Frames
- Downwards compatible to USB 2.0
- · LED indicator for link and activity
- USB bus powered
- Colour: black
- Cable length incl. connectors: ca. 12.7 cm

### System requirements

- iPad Pro (2018)
- Linux Kernel 2.6.x or above
- Mac OS 10.9 or above
- Windows 8.1/8.1-64/10/10-64/11
- Device with a free USB Type-C<sup>™</sup> port or with a free Thunderbolt<sup>™</sup> 3 port

### Package content

- USB Type-C™ Gigabit LAN adapter
- User manual

#### Images





## General

Supported operating system:	Linux Kernel 2.6 or above Mac OS 10.9 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit iPad Pro (2018)
LED indicator:	power and activity

## Interface

Connector 1:	1 x USB 5 Gbps Type-C™ male
Connector 2:	1 x Gigabit LAN RJ45 jack

## **Technical characteristics**

Chipset:	Realtek RTL8153
Data transfer rate:	Ethernet up to 10 Mbps Fast Ethernet up to 100 Mbps Gigabit Ethernet up to 1000 Mbps
Operating temperature:	0 °C ~ 55 °C

# **Physical characteristics**

Colour:
---------